

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Charlevoix

(County)

Located In

Corner Code #

1. Public Land Survey	T	33N	R	5W	K-1
	T		R		
2. Property Controlling in Section	S		T	R	
	S		T	R	
3. Miscellaneous Property in Section	S		T	R	
	S		T	R	

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on July 24, 2002 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-1 G.L.O. John Mullet June 1840 Set post for corner.

Wit: Sugar 12 N63°W 20 links

Sugar 10 N63°E 24 links

E.K. Robinson 1894 Sketch of section 2, Found in book 32A County Survey Records shows he had a corner position for this corner. No witnesses or type of monument was given.

Liber 443, Page 491 July 1990 Mary Feindt P.S.#03920 found 1/2" rod with P.S. cap #28417. She recommended that Emmet and Charlevoix counties agree to this corner as being the boundary between the two counties in July 1990.

Wit: 14" Maple N83°E 16.30'
8" T. Maple S07°W 14.91'

Liber 353, Page 903 Robert F. Mitchell, Aug. 1985

Set 1/2" X 18" rered with P.S. Cap #28417.

Wit: 8"-10" Twin Maple S04°W 14.86'

12" Maple N88°E 16.15'

Corner fence post S20°W 22.86'

"T" iron 15410 N10°04'22"E 204.32'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-1 Found and accepted 1/2" rod with P.S. cap #28417 as set by Robert F. Mitchell.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-1 Found 1/2" rod with P.S. cap #28417

Wit: 12" Maple S85°E 16.39'

20" Twin Maple S14°W 14.89'

8" Triple Maple N80°W 31.23'

4" Maple N23°E 42.95'

Fence going South and West



Signed by:

Carl T. Kiiskila

Date:

12-19-02

Surveyor's Michigan License No.:

33981