SURVEY & REMONUMENTATION

FEB 2 2 2001

STATE OF MICHIGAN COUNTY OF CHARLEVOIX RECEIVED YOR VEORD

SECTION

LAND CORNER RECORDATION CERTIFICATE 00 DEC 21 AM 9: 11

ins garners in	Filing Requ	uirement of Act 74, Mich.	P.A. 1970 UU UEU ZI AM 3111
Charlevolx L	ocated In:	Corner Code #	Charge 13. Destry
2. Property Controlling in Section S 3. Miscellaneous S Property in Sec. S	T 33N R 8W T R T R T R T R T R T R T R T R T R T R	<u>C-11</u>	REGISTER OF DEEDS Register of Deeds Stamp & File Nur
4. Lot No, Recorded Pla	t		
5. Private Claims			A B C D E F G H I J K
i. Wavne E. Boss in a field su	nvevinn October 20	D 2000 da harabu atata (b.s.)	2 6 5 4 3 2 3 3 4 7 8 9 10 11
requirements of P.A. 74, Michigan P.A. of were in conformance with regulations and instructions of the United States Department of a Court of Law and for that the conconformance with the rules of the Michigan established, re-established, monumented, reconformance.	1970, the corner poir rules therefore as requit of the Interior, Bureaumer points mentioned to Board of Land Survey	nts mentioned in lines 1 and 2 a uired in the current manual of si u of Land Management or by a de in lines 3, 4 and 5 above we	bove 6 10 17 16 15 14 17 16 15 14 17 16 15 14 17 17 18 17 18 17 18 18 19 19 19 19 19 19 19 19 19 19 19 19 19
NOTE: Not more than 2 corners, all in on this certificate.	ı the same town and	range, may be recorded	11
A. Description of original monume restoration:	nt and accessories	s and/or subsequent	13
C-11 October 1841 Charles W. Cathcart D.S Set Section comer post 1) Hemtock 10" N65"W 3 links (1.98") 2) Hemtock 6" S 70°E 20 links (13.2")	Found 3) P.P	5, 1972, A.V. Courtright 15/8" iron in toad P. S 60°W 43.01, PPN 60°E 57.91 . S60°E 63.28"	May 10, 1974 M.C. Feindt, used corner No witness noted
About 1975, L.R. Feindt, P.S. ound 1/2' rod 1) Power pole N74"30"E 57.50' 5) Power pole S 61"E 63.0' 5) Power pole S71"E 63.28'	Used i	0, 1988 J.E. Ferguson, P.S. fron as found nesses noted	Chailevoix Co. Surveyor AFPBOVED Signature Mary C. Feunde Dato: 1212-22
3. Description of corner evidence for	and/or method:	applied in restoring or reesta	
C-11 October 2000 Cound 1/2" iron in road intersection) Power pole N74°30°E 57.50' found nail and		•	•
C-12 to C-11 GLO 40 chains (2640) measure C-11 to C-10 GLO 40 chains (2640) measure			
Description of monument for corner The Placed Charlevoix County steel marker	and accessories es and monument box;	stablished to perpetuate locat	ing the position of the corner:
Power pole N75° 30'E 57.50 Found nail and Street sign N45°W 38.36' Bellriser S39°E 45.20' 10" Twin Oak S40°W 62.70 pladed nail	Itag		
nd is accepted as a careful and taithful reesta	plishment of the position	n of the original corner.	
gned by	70300	Date 12	115/2000
// 3.1	District \$	_ I	