

**FEB 22 2001**

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF CHARLEVOIX  
RECEIVED FOR RECORD

00 DEC 21 AM 9:12

For corners in

Charlevoix Located In: Corner Code #  
(County)

1. Public Land Survey T 33N R 8W C-12  
T R  
T R  
T R
2. Property Controlling S T R  
in Section S T R
3. Miscellaneous S T R  
Property in Sec. S T R

REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Wayne E. Boss, in a field survey on October 20, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

C-12 October 1841, Charles W. Cathcart D.S.

Placed quarter post

1) Beech 6" N 30° E 18 links (11.88')

2) Beech 6" N45°W 12 links (7.92')

About 1900 D.C. Nettleton

Placed corner per J. Dixon's notes

April 1973 A.V. Courtright

Antrim County Resurvey notes,

Used Nettleton's corner and placed witness

3) Maple cluster East 30.05'

4) 8" Maple S85° W 20.53'

5) 19" Triple maple N45°W 26.25'

May 10, 1974

M.C. Feindt P.S.

Fd. D.C. Nettleton's corner and re-witnessed with nails

3) Maple cluster East 30.03' placed nail and tag

4) 8" Maple S 85° W 20.53' placed nail and tag

5) 19" Triple Maple N45°W 26.25'

Charlevoix Co. Surveyor

APPROVED

Signature Mary C. Feindt

Date: 12-1-00

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

C-12 November 3, 2000

Found witness by N.C. Feindt

Reset corner from witness

Fell in C.L. of N.S. gravel road

Found old fence to West and down the hill

GLO C-13-C-12 40 chains (2640') MCF 2520.87 Measures 2518.75'

C-12-C-11 40 chains (2640') measures 2648.27'

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

C-12 Placed Charlevoix County steel marker

3) Maple cluster East 30.03'

4) 8" Maple S85° W 20.53'

5) 19" Triple Maple N45°W 26.25'


6) 6" Maple S11°E 87.08'

And is accepted as a careful and faithful reestablishment of the position of the original corner.

Signed by Wayne E. Boss

Date 12/15/2000

Surveyor's Michigan License No. 20703



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1976

REVISED JAN., 1981

REVISED OCT., 1996