

FEB 22 2001

STATE OF MICHIGAN
COUNTY OF CHARLEVOIX
RECEIVED FEB 1 2001

00 DEC 21 AM 9:03

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Charlevoix Located In: Corner Code #
(County)

1. Public Land Survey T 33N R 8W E-5
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

Charles B. Norton
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Wayne E. Boss, in a field survey on November, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

E-5 October 22, 1841 Charles W. Cathcart, D.S.
Set post at section corner
1) Beech 4" S40° W 14 links (9.24')
2) Beech 10" S80° E 25 links (16.5')

July 12, 1978 John E. Ferguson, P.S.
Found 1/2" rod
3) Power pole South 34.0'
4) Power pole N76° E 107.4'
5) 3" Apple N50° E 49.15'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-5 November 6, 2000
Found 1/2" rod 5' North of center line of East West gravel road.
3) Power pole South 34.0'
4) Power pole N76° E 107.40'
5) 3" Apple N50° E 49.15'

E-6 to E-5 GLO 40 chains (2640') from new E6 measures 2654.615'W
E-5 to E-4 GLO 40 chains (2640') measures 2643.61'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-5 Placed Charlevoix County steel marker
3) Power pole South 34.0'
4) Power pole N76° 107.4'
5) 3" Apple N50° E 49.15' found nail
Old fence to South
Power pole S 87° W 328.84 Placed nail 2643.61'

Charlevoix Co. Surveyor
APPROVED
Signature *Mary C. Peard*
Date: 12-07-00

And is accepted as a careful and faithful reestablishment of the position of the original corner.

Signed by
Surveyor's Michigan License No.

Date

12/15/2000

