

LAND CORNER RECORDATION CERTIFICATE

	Filing Req	uirement of Act 74, Mich. P.A.	1978U DEC 21 PM 2: 11
For corners in			Charama a a
Charlevoix	Located In:	Corner Code #	REGISTER OF DEEDS
(County)		4001	REGISTER OF DEEDS
1. Public Land Survey	T 33N R 9W	MC West of I-13	
	TR_ T 32N R 9W	MC West of I-1	
	TR		
2. Property Controlling	S TR S T R		
in Section 3. Miscellaneous	s TR		
Property in Sec.	s TR		Register of Deeds Stamp & File Number
4. Lot No, Rec	orded Plat		A B C D E F G H I J K L
5 Private Claims			2 6 5 4 4 3 7 2
_	····		3
		;	4 7 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
	- Sald currow on Novemb	er , 2000 do hereby state that unde	5 13 16 15 14 1
I, Wayne E. Boss , In requirements of P.A. 74, Mich	a neid solvey on <u>Novemb</u> ligan P.A. of 1970, the corner p	coints mentioned in lines 1 and 2 above	e 6 18 17 18 13 14 1
were in conformance with reg	ulations and rules therefore as i	nay of I and Management or by a decre	e 10 21 22 23 2
of a Court of Law and for	that the corner points mention	ed in lines 3, 4 and 5 above were in veyors or by a Decree of a Court of Law pressed below:	7, 9
conformance with the rules of established, re-established, mo	numented, recovered, found as ex	pressed below:	10 30 29 28 27 26 2
*	omers, all in the same town a		11
on this certificate.			$\frac{3}{1}$ $\frac{3}{1}$ $\frac{3}{3}$ $\frac{34}{1}$ $\frac{3}{3}$ $\frac{34}{1}$ $\frac{3}{3}$
			13
A. Description of origin	al monument and accesso	ries and/or subsequent	V
restoration: MC June 5, 1839 John Hodgs	on D.S. June 1967	MC Feindt	SURVEY &
Set nost	SHOWS HOTH		REMONUMENTATION
1) Cedar 10" N 59" E 21 links 2) Cedar 10" S 25" E 46 links			
About October 1999 John E. F	erguson & Associates		FEB 2 2 2001
Set object 138.85' West of roa and 1.5' North of old fence	dway		(%) The second of the second o
			SECTION
B. Description of corner	evidence found and/or meth	od applied in restoring or reestabli	shing corner:
MC October 2000	e (1" diameter hexagonal , ipossi	ble old gun barrel])	
24' East of high water mark an	d 125. East or existing edge of wi	·	•
I-13 to Mc GLO 14.98 chains	(988.68) measures MLF 1967 88	3.31', WEB Nov. 15, 2000 883.81'	the english of the corner
		es established to perpetuate locati	ng the position of the comon
MC Placed Charlevoix County	steel marker directly East and ac	ljacent to gun barrell	
3) 6" Maple N 29° E 13.00° pl	aced nail		
4) 10" fron Wood N 62° E 11. 5) 10" Maple S 35° E 20.64 p	laced nail	:	Charlevoix Co. Surveyor
6) 6" Cedar S25" E 15.00 pla	ced nail		APPROVED
		•	Signaturo Mary C. Feindt
	and faithful reestablishment of the	position of the original corner.	Signaturo Many C. Ferndt
And is accepted as a careful	d Janifica Teesday		
//	former gen		/ /
M	Y was the contract of	Date	2/15/2000
Signed by	NO X X Z WAYNER.	* Date	1
Surveyor's Michigan License	/ HOSS	m .	
- //	PROFESSIONAL	10,1	
ν	No. 20703	T W F	
	The state of the s	A Par	
	PROFESSIONAL SURVEYOR NO. 20703	FORM APPROVED B	Y MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 2
	**************************************	. *****	REVISED MAY