

# SURVEY & REMONUMENTATION

FEB 22 2001

## SECTION

### LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF CHARLEVOIX  
RECEIVED FOR RECORD

01 JAN 17 AM 11:59

*Charles M. Jost*  
REGISTER OF DEEDS

For corners in

Charlevoix

(County)

Located In:

Corner Code #

1. Public Land Survey

T 33NR 9W K-13 ✓

T R

T 32NR 9W K-1

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Wayne E. Boss

DECEMBER 19 99

I, \_\_\_\_\_, in a field survey on \_\_\_\_\_, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	N
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-13 JUNE 5, 1839

JOHN HODGSON, DEPUTY SURVEYOR  
SET SECTION CORNER POST  
BEECH 7 INCH N36°E 18 LINKS  
SUGAR 10 INCH N42°W 25 LINKS

MARCH 30, 1964

MATT KOVISTO, SURVEY CHIEF MSHD  
FD. RED & GREY STONE WITH + ON TOP  
PLACED 5/8" IRON BAR  
28" MAPLE N75°E 90.18'  
19" MAPLE S65°E 70.15'  
25" MAPLE S22°E 46.49'

NOV. 7, 1978

NB DEYOUNG, RLS  
FOUND IRON  
WITNESSES NOTED  
BUT NOT READABLE

JULY 29, 1997 JE FERGUSON, PS  
FD. IRON

30" MAPLE S30°E45.5', PWR. POLE  
N80°W 32.85', 3/4" PIPE NORTH 330.0'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-13 DECEMBER 8, 1999

FOUND 5/8" ROD IN CENTER OF EAST - WEST GRAVEL ROAD  
36" MAPLE N75°E 90.18'  
22" MAPLE S65°E 70.15'  
25" MAPLE S22°E 46.49'

REMAINS OF FENCE LINE TO SOUTH

L-13 TO K-13 GLO 40 CHAINS (2640') MSHD SHOWS 2606.08', MEASURES 2603.89'

K-13 TO J-13 GLO 40 CHAINS (2640') MCF SHOWS 2601.2', MICH. DNR SHOWS 2599.76'

Charlevoix Co. Surveyor

APPROVED

Signature *May C. Ferndt*

Date: *12-7-01*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-13 PLACED CHARLEVOIX COUNTY STEEL MARKER IN ROAD  
36" MAPLE N75°E 90.45' SET NAIL & TAG  
22" MAPLE S65°E 70.58' SET NAIL & TAG  
25" MAPLE S22°E 46.18' SET NAIL & TAG  
POWER POLE SOUTH 105.92' SET NAIL & TAG

AND IS ACCEPTED AS A CAREFUL & FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER

Signed by

Surveyor's Michigan License No. *20703*

Date *12/23/99*

