

SURVEY &  
REMONUMENTATION

MAY 05 1997

RE MONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
**Cheboygan**  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 33N R 3W M-3

T R

T 33 R 02 A-03

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Brian K. Fullford, in a field survey on August, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.	1960 LCRC In County Surveyor	1964 LCRC Recorded Survey
Set Section Corner Post	Corner Records	Liber A, Page 61
14" Beech S10°W 31 Links	Dean DeLamater #5778	Orlando Doyle #7319
10" Sugar N26°E 22 Links	Fnd "X" In Large Stone	Fnd Boat Spike
	Set Boat Spike	3 DeLamater Witnesses
	15" Maple N53°E 40.04'	
	18" Elm N32°W 41.04'	
	12" Elm S55°E 46.17'	

Paul Richards Hilltop Add'n  
To the Village of Wolverine  
Recorded in Liber 4, Page 3  
Cheboygan County Records

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fnd PK Nail on top of Boat Spike in Center Line of Asphalt Road.  
Concrete Monument 33' South (Paul Richards Hilltop Add'n)  
27" Maple N53°E 40.04' (DeLamater Witness)

LIBER 010 PAGE 191

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-3 Fnd PK Nail on top of boat spike in Center Line Asphalt Road. Replaced with 5/8" x 36" Bar with Remonumentation Cap in Monument Box. Accepted as a careful & faithful re-establishment of the position of the original corner.

Concrete Monument 33' South and 165' West Per Plat of Paul Richards Hilltop Add'n  
27" Maple N53°E 40.04' Set Tag  
P. Pole S63°E W/PK @ 54.55'  
6" Tw Apple S65°W Set Tag @ 87.01' 3/4/97 B.K.F.  
P. Pole N14°W 20.40' W/60p

THIS CORNER IS ALSO DESIGNATED AS CORNER CODE #A-3, IN T33N-R2W

Signed by B. K. Fullford

Surveyor's Michigan License No. 41099

Brian K. Fullford, PS

Date 10/22/96

RECEIVED  
FOR RECORD

96 NOV 25 PM 12:47

James J. Gray  
CLERK/REGISTER  
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

