

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Cheboygan

(County)

Located In

Corner Code #

1. Public Land Survey	T		R	
	T		R	
2. Property Controlling in Section	S 12	T 34N	R 1W	1
	S 12	T 34N	R 1W	10
3. Miscellaneous Property in Section	S	T	R	
	S	T	R	

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on April 28, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11				
5													
6	18		17		16		15		14				
7													
8	19		20		21		22		23				
9													
10	30		29		28		27		26				
11													
12	31		32		33		34		35				
13													

A. Description of original monument and accessories and/or subsequent restoration:

1-W 1/16 Cor. comm. to sec.'s 1 & 12, T34N,R1W

10-S 1/16 Cor. comm. to sec.'s 11 & 12, T34N,R1W

None

None

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

1-W 1/16 Cor. comm. to sec.'s 1 & 12, T34N,R1W

10-S 1/16 Cor. comm. to sec.'s 11 & 12, T34N,R1W

Found and accepted a 1/2" CIR #15410 as set by D. Porter fitting the standard BLM procedure for the subdivision of a section.

Set stamped 2" dia. alum. cap on 5/8"x34" rebar 6" below grade, per standard BLM procedure. Corner falls 2' east of N-S c/l gravel road. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-W 1/16 Cor. comm. to sec.'s 1 & 12, T34N,R1W

10-S 1/16 Cor. comm. to sec.'s 11 & 12, T34N,R1W

1/2" Capped Iron rod w/P.S. cap#15410

Stamped 2" dia. aluminum cap on 5/8"x34 rebar

Witnesses:

S85°E 12.85' to set N&T on N side 16" W. Pine  
S03°E 18.85' to set N&T on E side 4" B. Flr  
S49°W 25.88' to set N&T on SE side 6" B. Spruce  
N36°W 25.62' to set N&T on SW side 6" R. Maple  
Set Blue Carsonite Post w/location tag 1' North

Witnesses:

N87°E 87.00' to set PK&T on N side P.Pole  
S41°E 79.81' to set N&T on SW side 13" R.Pine  
S34°W 52.78' to set PK&T on SE side P.Pole  
S63°W 53.36' to set N&T on SE side 14" R.Pine  
Set Blue Carsonite Post w/location tag 50' East

Signed by:

Carl T. Kiiskila

Date:

6-15-10

Surveyor's Michigan License No.:

33981

