

# REMONUMENTATION

*North*  
MAY 5 1987  
COMMISSION

## RE MONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Cheboygan

(County)

Located In:

Corner Code #

1. Public Land Survey

T 34N R 3W

M-12

T 34 R 2W

A-12

2. Property Controlling  
in Section

S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R     

S      T      R     

4. Lot No.         , Recorded Plat         

5. Private Claims         

RECEIVED  
FOR RECORD

96 NOV 25 PM 12: 59

*James E. Gray*  
CLERK/REGISTER  
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

I, Brian K. Fullford, in a field survey on August, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.

Set 1/4 Section Post

18" Hemlock N70°E 5 Links

8" Cedar S82°W 18 Links

1978 Unrecorded Survey By R.C.Dunn  
No Wits or Corner Identified

1995 Unrecorded LCRC  
By Porter Survey

Set By Single Proportion

8" Aspen N87°W 13.94'

6" Aspen N01°E 18.35'

8" Aspen N61°E 13.19'

5" Ash S04°E 4.92'

Set by Single Proportion

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fd 1/2" Bar & Cap #33984

8" Aspen N87°W 13.94'

6" Aspen N01°E 18.35'

8" Aspen N61°E 13.19'

5" Ash S04°E 4.92'

LIBER 010 PAGE 202



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-12 Fnd 1/2" Bar & Cap #33984, Replaced with 5/8" x 36" Bar with Remonumentation Cap. Accepted as a careful & faithful re-establishment of the position of the original corner.

6" Aspen N01°E 18.35'

8" Aspen N61°E 13.19'

5" Ash S04°E 4.92'

8" Aspen N87°W 13.94'

On Se'ly Edge of Old R.R. Grade Sw'ly 100'

To River Nw'ly 70' to River

THIS CORNER IS ALSO DESIGNATED AS CORNER CODE #A-12, IN T34N-R2W.

Signed by

*B. K. Fullford*

Surveyor's Michigan License No.

41099

Brian K. Fullford, PS

Date

10/22/96

