## LAND CORNER RECORDATION CERTIFICATE

			Filing	Requi	rement of	Act 74, N	vlich. F ∫	PA 1970					
For Corners In: Cheboygan (County)		Lo	cated in		Corner (	Code #	ļ						
1. Public Land Survey		<u> </u>	R										
Property Controlling in Section	S 5			3W	2								
Miscellaneous     Property in Section	\$_5 \$	- ' <u>-</u> 3 - T -	R	3W	6_				Panistar of	Daarle St	amp & File Nun	nhos	
4. Lot No:	Recorde	d Plat:					_		togiotoi oi	<u> </u>	amp ar ne trai	IIDel	
5. Private Claims:	<del>.</del>							1 A B 2 - 6 -	C D E	F G	H I J K	L M	
I, <u>Carl T. Kiiskila</u> , in a field requirements of PA 74, Mic and 2 above were in conforthe current manual of sun Interior, Bureau of Land Ma corner points mentioned in of the Michigan Board of established, re-established,	chigan PA ormance with vey instruct nagement or lines 3, 4 a Land Sur monument	of 1970, in regulations of or by a dind 5 aboveyors of ed, reco	the corner tions and the Unite ecree of a ove were or by a vered, for	er points rules the ed States a Court o in confor Decree und as ex	mentioned erefore as respectively. The partment of Law and/or mance with of a Court expressed be	in lines 1 equired in ent of the or that the the rules of Law; low;		3	8	-16 -1	5 -14	12	
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.										-28 2	7 25 3	25	
A Description of original	monumor	of and a		11	1			13	<del> </del>		<del></del>	<b></b>	
<ul><li>A. Description of original</li><li>2-This corner position</li><li>Government Survey.</li></ul>								nosition	) was no	t ootobl	ished in the		
B. Description of corner e	evidence fo	ound ar	nd/or me	thod app	plies in res	toring or re	e-estab	lishing c	orner:				
2-Established the Northwest corner of the Northeast quarter of the Northeast quarter of section 5 as per B.L.M. instructions for the subdivision of a section.							6-Established the Southwest corner of the Northeast quarter of the Northeast quarter of section 5 as per B.L.M. instructions for the subdivision of a section.						
C. Description of monumers 2-Set 5/8" x 32" rerod with the side 4" N&T N side 4" N&T N side 4" N&T N side 4" N&T E side 6"	with P.S. Balsam Maple Balsam Balsam	cap #3 N8 N1 S 8	I accesso 3981 87°E 10°W 37°W 6°W	25. 14. 24.	03' 75'	6- Set 5	8" x 3 N&T N&T N&T N&T	2" reroo W side S side W side	position of with P.S 4" Ironw F. Post 8" Maple 8" Maple	S. cap # rood e		21.01' 3.12' 36.33' 24.67'	
Signed by: Surveyor's Michigan Li	al icense No	<u>T JK</u> ::	3398		î ORM APPRO	Date: VED BY MIC		8-1	18-0	8	SURIE OF KIIS LA SURI NAL SURVEY REVISE RE	ARL SKILA IND VEYOR 0.	