

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. <u>34</u> N. R. <u>3</u> W.	<u>J-9; J-8; J-7</u>
2. PROPERTY CONTROLL- ING IN SECTION_____	T. _____ N. S. R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION_____	T. _____ N. S. R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on FEBRUARY 4, 1983, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- J-9 - SET CORNER BY SINGLE PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS.
NO EVIDENCE OF A PREVIOUS CORNER.
- J-8 - SET CORNER AT CALCULATED INTERSECTION OF TRUE 1/4 LINES PER STANDARD
SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.
- J-7 - FOUND IRON BAR IN PLACE, APPARENTLY A PERPETUATION OF BOWEN 1908 SURVEY.
USED IN SURVEYS IN SECTION 14.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>J-9</u>	<u>J-8</u>
SET DNR MONUMENT	SET 5/8" ROD WITH RLS CAP
8" S. MAPLE N38°W 28.0'	12" CHERRY N1°E 20.5'
5" S. MAPLE N60°E 24.7'	7" ASPEN S48°W 15.0'

J-7
LEFT IRON BAR IN PLACE
6" R. PINE S 32°E 58.5'
14" S. MAPLES S 30°W 55.9'

SIGNED BY Kenneth J. Ostling

DATE 10/28/83

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ CHEBOYGAN COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET