

1998

1998

SECTION

CHEBOYGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Cheboygan

Located In:

Corner Code #

(County)

1. Public Land Survey

T 36N R 3W D-3
T R
T R
T R
T R
S T R
S T R
S T R
S T R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

RECEIVED FOR RECORD 1-8-99
at 9:00 O'Clock A M

Joanne Spray

CLERK/REGISTER
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Brian K. Fullford, in a field survey on June 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	19			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

1855 Harvey Mellon
Resurvey
Set 1/4 post
10" Aspen N 52° W 7 lks
10" Aspen N 8° E 5 lks

1970 Doyle Civil Engineers
Unrecorded Survey

Jan 1973 Orlando Doyle #7319
Conc Mon in place
No wits given

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fnd conc mon w/U of M cap & RLS #7319
Fnd 3" X 3" Sq. Cedar post lying down
21' +/- West of Old North/South Two track
36" +/- North of Old East/West Dr.

Janet H. Chang

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-3 Use existing concrete monument with U of M cap & RLS #7319, and position is accepted as a careful and faithful perpetuation of the original corner.

4" Tw. Basswood N 6° E 14.46' Set tag 41099
8" Ash N 79° E 38.50' Set tag 41099
13" Poplar S 7° W 5.95' Set tag 41099
5" Maple N 70° W 20.41; Set tag 41099

Signed by *B. K. Fullford*
Surveyor's Michigan License No. 41099

Date 11/23/98

