

SURVEY &
REMONUMENTATION

FEB 26 1998

CHEBOYGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION

Cheboygan

(County)

Located In:

Corner Code #

1. Public Land Survey

T36N R 3W

Other
#2

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

RECEIVED FOR RECORD 12-18-97
at 10:58 O'Clock A M

Joanne Spray

CLERK/REGISTER
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

I, Brian K. Fullford, in a field survey on Sept, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.
1855 Harvey Mellen
Set meander post
12" Spruce N 3° W 2 lks
10" Aspen S 16° E 14 lks

DeLaMater-Muschell
Unrecorded
Section Index Map

1961 Supervisor's Plat
of Greenman's Pt.
Dean DeLaMater #5778
Concrete Monument & Plat

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Axle found 4.2' North of Section line, and concrete monument and lot corners for Greenman's Point Plat recovered 33' South of Section Line. No witnesses found. Deflection angle at North 1/4 post agrees within 1 minute of DeLaMater-Muschell Survey using Greenman's Point monumentation. DeLaMater's work appears to be the only recorded evidence of this corner, origin of other monumentation is unknown. Measured 2382.46 feet from N 1/4 corner to water's edge, versus 2382.60 feet to G.L.O.

LIER 011 PAGE 02

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-5 to J-5

Placed 5/8" rebar with remonumentation cap, and position is accepted as a careful and faithful reestablishment of a witness corner to the original meander corner.

6" Ash N 66° E 39.74'
22" Maple S 49° E 42.34'
13" Ash S 16° E 32.36'
4" Ash N 64° W 24.00'
Axle N 79° W 21.54'
Edge of water West 42'

Signed by B. K. Fullford
Surveyor's Michigan License No. 41099

Date 11/21/97

