

SW 1/4 1899

1998
CHEBOYGAN COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Cheboygan

(County)

Located In:

Corner Code #

1. Public Land Survey

T^{36N} R^{3W}

10

2. Property Controlling
in Section

S T

T R

3. Miscellaneous
Property in Sec.

S T

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Brian K. Fullford, in a field survey on June, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1855 Harvey Mellon
Resurvey
Set meander post
9" Tamarak N 4° E 33 lks
12" Cedar S 55° W 30 lks
Cedar swamp to lake

1970 Doyle Civil Engineers
Unrecorded Survey

1997 Brian Fullford Set 1/2" Bar
w/cap #41099
Unrecorded Survey
No witnesses

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Find 1/2" Bar w/cap 41099
8" Spruce N 21° E 16.34'
9" Ash N 72° E 15.74'
11" Ash S 15° W 5.72'
10" Maple S 64° W 12.36'
High water mark East 20' +/-

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E3-F3 Replaced 1/2" bar & cap with 5/8" rebar with remonumentation cap, and position is accepted as a careful and faithful perpetuation of a witness corner to the original corner. Monument is 257.42' East of the Northwest corner of Section 9, T36N-R3W. Witness corner is 31.7' West of original Meander corner.

8" Spruce N 21° E 16.34' Set tag 41099
9" Ash N 72° E 15.74' Set tag 41099
11" Ash S 15° W 5.72' Set tag 41099
10" Maple S 64° W 12.36' Set tag 41099
High water mark East 20' +/-

Signed by B. K. Fullford
Surveyor's Michigan License No. 41099

Date 11/23/98

RECEIVED FOR RECORD 1-8-99
at 9:04 O'Clock A M

Joanne Spray

CLERK/REGISTER
CHEBOYGAN COUNTY, MICHIGAN

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

