

MAR 3 8 1999

1998

CHEBOYGAN COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION	- Care	lling Requ	irement of Ac	74, Mich. P.A.	1970										
Cheboygan	Located In:	Co	Corner Code #			RECEIVED FOR RECORD 1-8 99 at 9.06 O'Clock 4 M									
(County)					ct _	<u></u>	7.0	10	_O'CI	ock	4	,М			
1. Public Land Survey	T <u>37N</u>	R <u>3W</u> R <u>3W</u> R		>~		J	Od.	rın	(Å	g. Old	y				
T R								CLERK/REGISTER CHEBOYGAN COUNTY, MICHIGAN Register of Deeds Stamp & File Number							
4. Lot No, Record	rded Plat				į	A B	С	D E	F	3 H	I J	к	L M		
5. Private Claims					1 2			ĪĪ	Ţ	Ţ	ŢŢ	Ť	Ţ		
					3	Ľ									
Brian K. Fullford	, in a field survey o	_n June	, 19 ⁹⁸ do h	ereby state that unde	r 4	<u>1</u>		- 8 -	_ 9	10_	 	<u> </u> ;	 12		
conformance with regulations and	in P.A. or 1970, the co I rules therefore as requ	orner points r uired in the cu	nentioned in lines : irrent manual of su	i and 2 above were if	n e 5			+					-		
United States Department of the that the corner points mentioned	Interior, Bureau of Land	d Managemer	nt or by a decree of	a Court of Law and /o	اء ت	1,8	-	-17-	16	 15	-14-		ا رع۔۔۔۔		
Board of Land Surveyors or by recovered, found as expressed be	a Decree of a Cour	t of Law; es	tablished, re-estat	lished, monumented	· '			++			 	+	H		
•					9	—19 		20-	-21 	22	 23 -	 2	4		
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.						36		20	20	27		1,			
or and obtained.					10 11										
					12	 31	_	32	_33	 34	 35-	3	36		
					₁₃ [Ш.							
A. Description of original mo	nument and access	ories and/o	r subsequent res	toration:											
1840 John Mullett Original Survey Set Post 9" Hemlock N 24° W 8" Hemlock N 65° E		#7319 F W. Pine W. Pine	oyle Civil Engir Fnd 1" pipe S 75° 30' E 5 S 74° 30' W 2 N 17° 30' E 4	0.36' :3.69'											
B. Description of corner evid Fnd Conc Mon w/U of 13" R. Pine N 15° E of 13" R. Pine S 77° E of 13" R. Pine S 72° W	of M cap & RLS # 46.38' w/ old tag 50.07' w/ old tag		olied in restoring	or reestablishing co	orner: .			ans	H	Gra	y	A CONTRACTOR OF THE PARTY OF TH			
C. Description of monument	for corner and acces	ssories esta	blished to perpet	uate locating the p	osition	of th	e co	ner:							
G-1 Use existing and faithful p	concrete monumerpetuation of the	ent with U e original c	of M cap & RL	.S #7319, and po	osition	is a	ccep	ted a	s a ca	areful	La .				
1 8 1	3" R. Pine N 15° E 3" R. Pine S 77° E " Poplar S 23° W 3" R. Pine S 72° V	E 50.07' 28.59' N 23.68'	w/ old tag w/ old tag Set tag 41 w/ old tag				44444	THE THE ST	FUL	IAN K LFOR	RD NAL	* H(
Note: THIS CORNE	_	IGNATED	CODE G-13	IN T37N-R3W.			*	型	SUI	RVEYO! No .	R j	$\tilde{\omega}$			
D VO	-11)			,			7	(O, 1	. 4	1099		÷ 3			

// 41099

Signed by

Surveyor's Michigan License No.

OF ESSION