

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In: CHEBOYGAN (County)
Located In
Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Section
4. Lot No:
5. Private Claims:

I, Carl T. Kiiskila, in a field survey on February 7, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 and two dots in row 6, column C.

A. Description of original monument and accessories and/or subsequent restoration:
6- NE 1/16 corner, section 18, T38N, R02W
9 - CE 1/16 corner, section 18, T38N,R02W
None
None

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:
6- NE 1/16 corner, section 18, T38N, R02W
9 - CE 1/16 corner, section 18, T38N,R02W
Set stamped 2" dia. aluminum cap on 5/8"x 34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner.
Set stamped 2" dia. aluminum cap on 5/8"x34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
6- NE 1/16 corner, section 18, T38N, R02W
9 - CE 1/16 corner, section 18, T38N,R02W
2" dia. stamped aluminum cap on 5/8"x34" rebar.
2" dia. stamped aluminum cap on 5/8"x34" rebar.
Wit: N74°E 20.61' to set N&T on N side 2" B. Fir
S55°E 14.88' to set N&T on SW side 9"&11" R. Maple
S06°W 23.00' to set N&T on NW side 3" B. Fir
N68°W 9.00' to set N&T on SW side 2" B. Fir
Set Blue Carsonite Post w/ loc. tag 1' North
Wit: N48°E 30.87' to set N&T on N side 10" B. Fir
S16°E 31.65' to set N&T on W side 4" R. Maple
S47°W 31.95' to set N&T on N side 5" R. Maple
N13°W 15.97' to set N&T on E side 4",5",9",15" R. Maple Clump
Set Blue Carsonite Post w/ loc. tag 1' West

Carl T Kiiskila
Surveyor's Michigan License No.: 33981

