STAVEVE

Cross	m ( ) ( )	CY &	
REMO	ONLINE	ERITATIACHI	EBOYGAN COUNTY REMONUMENTATION CORNER
	an . 43 (*** 813.1) E	- N 1 14 1 ( P. 11/2)	EBOYGAN COUNTY REMONUMENTATION CORNER LAND CORNER RECORDATION CERTIFICATE
			Filing Requirement of Act 74, Mich. P.A. 1970
. 8	MAYAF	100m	,g ,

CHEBOYGAN  COMMISSION Located In: Corner Code #	
COMMISSION Located In: Corner Code #	RECEIVED
1. Public Land Survey T 38N R 3W M-3 T R	FOR RECORD
TR	96 OCT 30 PN 12: 08
2. Property Controlling S T R	Grannesday
3. Miscellaneous S T R	CLERK/REGISTER CHEBOYGAN COUNTY HICHIGAN Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat	
5. Private Claims	A B C D E F G H I J K L I
	3
	4 -7 - 8 - 9 - 10 - 11 - 12 -
I, JAMES H. GRANGER, in a field survey on OCTOBER 18, 19 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner po	96
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore required in the current manual of survey instructions of the United States Department of the Inte	rior, 9 19 20 21 22 23 24
Bureau of Land Management or by a decree of a Court of Law and /or that the corner pormentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Boar Land Surveyors or by a Decree of a Court of Law; established, re-established, monumen	d of 9
recovered, found as expressed below:	10 30 29 28 27 26 25
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.	12 31 32 34 35 36
	134
A. Description of original monument and accessories and/or subsequent restoration:	
1840 - Original Survey 12" Cedar at corner John Mullett	
1964 - DNR-LCRC Set 1" pipe w/4" brass cap	
Ken Larsen #10695	algan C
	crehoygan Count
B. Description of corner evidence found and/or method applied in restoring or reestab	lishing corner:
Found 1" pipe with 4" brass cap, one scribed witness and set four witnesses.	OCT 3 0 1996
LIBER 010 PAGE 170	ie alate
FIRST OTO PAGET 10	Vonumenta
C. Description of monument for corner and accessories established to perpetuate to also corner A-3.T38N.R2W	ocating the position of the corner.
also corner A-3,T38N,R2W	SECTION HE SECTION
8" Birch N 60°E 18.00'	PROPERTY IN
6" Birch \$44°E 15.89' 6" Birch \$08°W 9.28'	1301
4" Balsam N36°W 10.07'	
	we will a sufficient to the second
Signed by Jawes H Grange	
Surveyor's Michigan License No. 16041	