SURVEY & REMONUMENTATION

NOV 2 5 1998

Approved By Delta County
Land Survey Remonumentation
Peer Group Under Act 345 Of
P.A. Of 1990 On June 26, 1998

-	(MAGE	9	RECORD	O	*
	-	Ε.	1 1	l i	il N
1.7	_	~	1 6	2	3 %

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. I	P.A. 1970 acting Chairman
Located In: Corner Code ##	Recorded June 301998
40 N 20 U 7 C	E 9:00 BASK AM
1. Public Land Survey T 40 N R 22 W F-9 M.C.F/G-9 (22)	Walley C. Those
TR	
TB	Dolta County Reg. of Deeds
2. Property Controlling S T R in Section S T R	
3. Miscellaneous S T R	Register of Deeds Stamp & File Number
Property in Sec. S T R	
4. Lot No Recorded Plat	——— ABCDEFGHIJKL
5. Private Claims [F-9] N1/4 COR SEC 28 [M.C. F/G-9] REFERENCE MONUMENT	2 5 5 1 3 2 1
it is also con one ze thic. It is not become	3 4 3 7 7
V 7 73270	4 7 8 9 10 11 11
I,M.P. DAVIS, in a field survey on	yioned 5
in thes 1 and 2 above were in conformance with regulations and rules therefore as required	in the 18 17 16 15 14 13
current manual of survey instructions of the United States Department of the Interior, Bureau of Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4	/ Latiu Time Time Time Time Time Time Time Time
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decr Court of Law, established, re-established, monumented, re-monumented, recovered, four	ree of a
expressed below:	10 30 29 28 27 26 25
NOTE: Not more than 4 corners, all in the same town and range, may be recorded	
on this certificate.	12 31 32 33 34 35 36
CORNER POSITION REFERENCED IN PLAT OF 1ST ADDITION TO CITY OF GLADSTONE (LIBER "A" F/G-9 [M.C.] WOOD POST - A. MERRYWEATHER, D.S 1846 - (BEECH 08"-WEST-07 LINKS) (NO RECORD EVIDENCE OF CORNER RECOVERY AND/OR SUBSEQUENT RESTORATION SECTION LINE BETWEEN SEC'S 21 & 28 ESTABLISHED AND MONUMENTED EAST OF THE N1/4 COR GLADSTONE (LIBER "A" OF FLATS PAGE 24).	BRECH STUB 06""-N42'E-44 LINKS)
B. Description of corner evidence found and/or method applied in restoring or rees F-9 [N1/4 COR SEC 28] NO CORNER EVIDENCE FOUND. IDENTIFIED THE WEST LINE OF THE AS CITY OF GLADSTONE (LIBER "B" OF PLATS PAGE 51) AND EXTENDED IT NORTH THE PLAT THE W1/16 COR ON THE N. LINE OF SEC 28. EXTENDED LINE EAST FROM NW COR SEC 28 ESTABLISHED THE 1/4 COR ON THIS LINE AT A PROPORTIONATE DISTANCE EAST OF THE W	SESSOR'S PLAT NO.1 DISTANCE & ESTABLISHED THRU THE W1/16 AND DAVIS 11/16 CORNER. LAND SURVEYOR
F/G-9 [M.CREFERENCE MONUMENT] FOUND IN PLACE A 3/4" IRON PIPE MONUMENT AT THE IN NORTH LINE OF SEC 28 AND THE NORTH LINE OF THE PLAT OF SOUTH SHORE ADDITION ON PAGE 24) 30' SWLY FROM THE NELY CORNER OF LOT 7 OF BLK 2 OF SAID PLAT. EX FROM THE N1/4 COR OF SEC 28 THRU THE PLAT MONUMENT & ESTABLISHED THE M.C. AT WEST OF THE NORTH 1/4 COR. WHICH FALLS IN THE ASPHALT SURFACE OF 10TH ST. SE 20.34' WEST OF THE M.C. POSITION.	(LIBER *A° OF PLATS TENDED A LINE EAST THE "GLO" DISTANCE
C. Description of monument for corner and accessories established to perpetuate 1 F-9 SET, 8" BELOW SURFACE, A 5/8" X 18" REBAR W/A 3-1/4" CAP STAMPED TO ID THE COR SW COR OF HOUSE SW COR CONC SLAB MAPLE 22" 5/8"X20" IRON PIN & N31°W N40°E S22°W S35°E 48.05' 40.20' 31.00' 56.60'	
F/G-9 (REFERENCE MONUMENT) SET, 6" BELOW GROUND SURFACE, A 5/8" X 18" REBAR W/A 3- CHISELED CROSSES ON CONC WALK MAPLE 12" RED PINE 20" N45°W N45°E S23°W N82°E 2.95' 1.75' 57.70' 64.88'	1/4" ALUMN CAP STAMPED TO ID THE CORNER POSITION
NOTE: BEARINGS TO REFERENCE OBJECTS ARE MAGNETIC & DISTANCES ARE TO A NAIL IN THE	CENTER OF THE OBJECT UNLESS OTHERWISE NOTED
Signed by Date	le/26/98
Surveyor's Michigan License No. 16926	ENDM ADDROVED BY MIRUIGAN CTATE DOADD OF LAND SIDUEYORS IAN 20 1