

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF: DELTA CO. LOCATED IN:

CORNER CODE NUMBER

1. PUBLIC LAND SURVEY _____ T. 41 N. 24 E. 3 W. B-11

2. PROPERTY CONTROLLING IN SECTION _____ T. _____ N. _____ S. _____ R. _____ E. _____ W. _____

3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ S. _____ R. _____ E. _____ W. _____

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Frank J. Bray do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on May 13, 1974 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B-11 Woodpost:
Cedar 8" S10°W 13 links
Cedar 10" N68°E 9 links
Subsequent monument: Scribed woodpost

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-11 This corner was replaced from old scribed woodpost in proper bearing and distance from original Cedar B.T. now a stump with scribe marks on lower face.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1" iron pipe with 4" aluminum cap. All bearings are magnetic.

B-11 3" Spruce (NBT) S62°E 19.4'
4" Spruce (NBT) S65°W 17.4'
Original BT S10°W 8.6'

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Frank J. Bray DATE 6-17-74
(Frank J. Bray) (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 13575