

DEC 18 1995

COMMISSION

RECORDED

NOV 22 PM 2:31

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Dickinson

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 39N R 29W

J-3

T 39N R 29W

G-1

J-3 2 33 34  
11 G-1 4 3

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, James H. Moore, in a field survey on September 6, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

J-3 Original Corner - Post Set by J. H. Mullet 1849 G-1 Original Corner - Post Set by H. Brevoort 1848

Original Bearing Trees

18" W. Pine N01°E 52 Links

18" W. Pine S01°E 31 Links

Original Bearing Trees

10" Birch N66°E 22 Links

8" Birch N20°W 24 Links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-3 Found 2" Iron Pipe With 3 Bearing Trees as Per Sundberg, Carlson's Notes

Located on North-South Fence Line, 144' North of North Edge of Pine Creek

Record Research On File With Register of Deeds

G-1 Found 1-3/4" O.D. Iron Pipe Located at Fence Corner With One BT as Per Sundberg, Carlson's Notes

Fences Run East, West and South

Record Research On File With Register of Deeds

ACCEPTED BY THE DICKINSON COUNTY  
SURVEY PEER GROUP AS THE OFFICIAL  
CORNER UNDER MICHIGAN PUBLIC ACT  
345 OF 1990 AT A MEETING HELD ON

11-20-95

R.H.P.

COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-3 Set New Dickinson County Capped Aluminum Monument. Monument Stamped to Identify Corner. Referenced as Follows:

6" Spruce S80°E 35.70'  
6" Cedar S30°W 27.32'  
5" Sugar N82°W 20.85'  
6" Spruce N55°W 34.04'  
Carsonite Rail North 0.75'

G-1 Set New Dickinson County Capped Aluminum Monument on North Side of Existing 1 1/2" Pipe. Monument Stamped to Identify Corner. Referenced as Follows:

Carsonite Rail North 2.0'  
6" Cherry S85°E 47.84'  
8" Cherry S06°W 22.06'  
10" W. Birch N80°W 109.95'

Signed by

Surveyor's Michigan License No. 28423

Date

11/20/95

