

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. _____ N. _____ E. _____ S., R. _____ W.		
2. PROPERTY CONTROLLING IN SECTION <u>36</u> , T. <u>41</u> N. <u>28</u> W. W.		1 & 8
3. MISCELLANEOUS PROPERTY IN SECTION _____ , T. _____ N. _____ E. _____ S., R. _____ W.		
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		
		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Arthur O. Enger, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 1 (West 1/16 corner between Sections 25 and 36, T41N, R28W):

Corner 8 (West 1/16 corner on E & W 1/4 line of Section 36, T41N, R28W):
Neither of these corners established in original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 1: Established 6/17/75 on line between Sec. Cor. 1312.9 ft. W and 1/4 cor. 1312.9 ft. E. Corner falls in pavement of Foster City-Waucedah Road about 4 ft. E of W. edge of pavement.

Corner 8: Established 6/26/75 on line between W 1/4 corner 1322.7 ft. W and Center 1/4 cor. 1322.7 ft. E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 1: 1/4" x 2" square-shanked, round-headed case-hardened nail
Red Pine 24 N72°E (mag.) 44.0 ft. "BT"
Red Pine 24 S87°W (mag.) 60.1 ft. "BT"

Corner 8: 1" I.D. x 36" iron pipe with 3½" aluminum cap and ½" x 12" re-inforcing rod welded to bottom end.
Red Pine 6 S55°W (mag.) 27.4 ft. "1/16S, BT"
W. Pine 5 S36°E (mag.) 29.9 ft. "1/16S, BT"

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Arthur O. Enger DATE January 8, 1976

CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR

Arthur O. Enger

Michigan Department of Natural Resources

13581

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

