## STATE OF MICHIGAN DEPARTMENT OF NATURAL RESOURCES



## LAND CORNER RECORD

	COUNTY
	T 42 N R 28 W
DESCRIPTION OF CORNER 1/4 corner between Sections 5 and 8	
CORNER MONUMENT 1" 1.D. x 36" iron pipe with 4" alumin	num cap
DATE MONUMENT PLACED AND WITNESSED January 13, 1970	
WITNESSES TO CORNER Sugar Maple 5 N36°W (mag.)	21 1ks. "1/4S, NBT"
Sugar Maple 6 N66°E (mag.)	
AND	
CIRCLE CORNER REGISTERED	

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

Found a 4" x 4" x 4" squared cedar post and an 8' steel fence post in place, apparently long used for local metes and bounds surveys.

Monuments are neither equidistant distant from, nor on line between section corners to E and W (2638.7 ft. to E and 2652.9 ft. to W, with a 0'14' right deflection at the 1/4 cornerwhen proceeding westerly on section line.) However, it was felt that moving the corner would create too much disturbance of local surveys, so it was perpetuated as found.

Corner accepted as found.

SURVEYOR'S SEAL

SIGNED

REGISTERED LAND SUPPLYOR

DATE

December 21, 1971

DISTRIBUTION:

Arthur O. Enger

County Courthouse Area Forester (Regions I & II) District or Region Surveyor Forestry Div., Lansing