

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Dickinson (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 6 T 42N R 30W	3 (GCDB 100660)
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		6		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 04/28/14 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

North 1/16 corner common to Section 1 T42N-R31W and Section 6 T42N-R30W.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Established the position for the corner on the Range line between Township corner 1258.71' north and  
1/4 corner 1317.33' south, the position being proportionate to the dimensions given on the original  
U.S. plat of this township.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
10" Spruce S10°W 26.95' mrkd "1/16S BT"  
4" Poplar N50°W 22.55' do  
4" Poplar N55°E 5.75' do  
5" Poplar S60°E 33.15' do  
Set sq'd cedar post adjacent.  
7913539.754 N= 143530.221

E=

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).  
Coord. Ref.=NGS PID RL0240: N= 145070.957 m. E= 7907633.634 m.

Signed by Stephan J. Szyszkoski Date 05/07/2014  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division