## STATE OF MICHIGAN DEPARTMENT OF NATURAL RESOURCES

## LAND CORNER RECORD

	Dickinson 0	OUNTY
	T <u>43 N</u> R	29 W
DESCRIPTION OF CORNER 1/4 corner between Sections 35	and 36	
CORNER MONUMENT 1" I.D. x 36" iron pipe with 4" alumi	num cap	
DATE MONUMENT PLACED AND WITNESSED July 30, 1970		
WITNESSES TO CORNER Cedar 10 N 120W (mag.) 21.3	ft. "1/4S, NBT"	
Cedar 10 N87°E (mag.) 16.7	ft. "1/4S, NBT"	<u> </u>
AND		
CIRCLE CORNER REGISTERED		

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR RESTORED.

Corner re-established on line between section corners to north and south, but at a distance proportional to the record distance between the SW corner of Sec. 36 and a stream crossing south of the NW corner of Sec. 36. Distance south to SW cor. of Sec. 36 is 2616.4 ft.; distance north to south bank of stream is 2210.9 ft., and to NW corner of Sec. 36 is 2621.0 ft.

SURVEYOR'S SEAL

SIGNED

REGISTERED LAND SUPPEYOR

DATE January 24, 197

DISTRIBUTION: REGISTERED LAND STARTHUR O. Enger

County Courthouse Area Forester (Regions I & II) District or Region Surveyor Forestry Div., Lansing

R 4047 Rev. 10/68