

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF --	LOCATED IN --	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____ N. _____ E. _____ S. _____ R. _____ W. _____		
2. PROPERTY CONTROLLING IN SECTION <u>20</u> , T. <u>43</u> N. <u>XX</u> R. <u>29</u> <u>XX</u> W. _____		<u>10, 15, 16</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ E. _____ S. _____ R. _____ W. _____		
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		
		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on See Below, 19____, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 10: Not set on original survey nor subsequently apparently.
Corner 15: Not set on original survey nor subsequently apparently.
Corner 16: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 10: Established 5-27-81 midway and on line between $\frac{1}{4}$ corner north and section corner south.
Corner 15: Established 5-18-81 midway and on line between $\frac{1}{4}$ corner east and section corner west.
Corner 16: Established 5-20-81 midway and on line between $\frac{1}{4}$ corner west and section corner east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 10: Set 1" I.D.x32" iron pipe with 4" alum. cap.
30" Sugar N80E 9.9 ft. 1/16S,BT
9" Elm S39W 53.3 ft. 1/16S,BT
Corner 15: Set 1" I.D.x32" iron pipe with 4" alum. cap.
8" Spruce S37W 6.6 ft. 1/16S,BT
10" Maple N39E 26.5 ft. 1/16S,BT
5" Maple N37W 26.1 ft. 1/16S,BT
Corner 16: Set 1" I.D.x32" iron pipe with 4" alum. cap.
5" Cedar N76W 39.6 ft. 1/16S,BT
4" Cedar S56W 34.9 ft. 1/16S,BT
6" Spruce N10E 16.0 ft. 1/16S,BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

