

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Dickinson

(County)

Located In:

Corner Code ~~##~~

1. Public Land Survey

T 44N R 27W

B-5, A-5, A-6.

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, David B. Babbitt, in a field survey on 8/18/87, 19_____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-5. N1/4 corner of Section 18. Fir Post. Cedar 10 - N34W, 22 Lks.
Sugar 10 - S60E, 33 Lks.

A-5. NW section corner of Section 18. Wood Post. Maple 12 - S17W, 19 Lks.
Fir 6 - N23E, 19 Lks.
Y. Birch 12 - S84E, 34 Lks.
Y. Birch 20 - N40W, 27 Lks.

A-6. W1/4 corner of Section 18. Cedar Post.
Y. Birch 16 - S32W, 06 Lks.
DO 8 - N63E, 20 Lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-5. Set by single proportion to the GLO record between the NW and NE section corners of Section 18.

A-5. Set by single proportion to the GLO record using the section corner 1 mile south and the twp. corner 2 miles north.

A-6. Set by single proportion to the GLO record using the section corner 1/2 mile south and the twp. corner 2-1/2 miles north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-5. DNR Monument.	A-5. DNR Monument.	A-6. DNR Monument.
5" r.maple S88W, 8.7'	15" w.pine N56E, 34.9'	12" w.pine N40E, 18.1'
4" balsam S22W, 19.2'	10" w.pine S39E, 23.1'	10" w.pine N65E, 33.55'
8" balsam N79E, 19.0'	9" w.pine S72W, 5.1'	12" h.maple S30W, 27.1'
3" balsam, S65E, 12.9'	5" r.maple N47W, 18.5'	14" w.pine N74W, 36.8'

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Signed by David B. Babbitt
Surveyor's Michigan License No. 21558

Date 12-3-87