

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Dickinson

(County)

Located In:

Corner Code #

1. Public Land Survey

T 44N	R 27W	L1
T 44N	R 27W	K1
T	R	
T	R	
T	R	
S	T	R
S	T	R
S	T	R
S	T	R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

K1 Oct 20 2001

L1 Oct 25 2001

I, Paul R. Bressette, in a field survey on , 20 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

(L1) Quarter corner common to Sections 1 and 36. 1846: Austin Burt, DS. Set wood post witnessed by: Spruce 8 N08E 8 lks.; Spruce 5 N49W 18 lks. 1980: Charles F. Clark, RLS. Set 1/2" capped rebar by single proportion witnessed by: 6" Poplar N50E 13.08'; 4" Poplar S30W 12.56'; 3" Poplar S70W 12.50'; 4" Poplar 3.41'.

(K1) Section corner common to Sections 1, 2, 35 and 36. 1846: Austin Burt, DS. Set wood post witnessed by: Tamarack 7 N31W 7 lks.; Spruce 7 N36E 6 lks. 1850: John Burt, DS. Marked two additional witnesses during subdivision of T44N, R27W: Spruce 12 S37W 18 lks.; Spruce 10 S61E 10 lks. 1980: Charles F. Clark, RLS. Set 1/2" capped rebar by single proportion witnessed by: 5" Spruce N20E 12.81'; 3" Poplar N75E 12.10'; 3" Spruce S20E 11.97'; 4" Poplar S60W 15.64'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(L1) Found Clark's monument and witnesses as described. Two witnesses are live and standing (8" Aspen measured N50E 13.1'; 11" Aspen measured S30W 12.55'). One witness is a rotten stump (measured S79W 12.5'), the remaining witness is rotten pieces (measured N43W +/- 3.9'). Rebar was rewitnessed, a DNR monument was driven over top, and is accepted as a careful and faithful REESTABLISHMENT of the position of the original corner.

(K1) Found 1/2" rebar without cap and two witnesses. Witness listed as a spruce to NE was found to be a jack pine (5" Spruce N20E 12.81'-found 10" Jack Pine N11E 12.8'). Found 6" black spruce (3" spruce S20E 11.97'-measured S22E 11.95'). Rebar was rewitnessed as found, a DNR monument was driven over top, and is accepted as a careful and faithful REESTABLISHMENT of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(L1) DNR monument	(K1) DNR monument
6" Spruce N85E 30.65' (1/4S, NBT)	5" B. Spruce N27E 10.35' (S36, NBT)
6" Spruce S54E 19.25' (1/4S, NBT)	5" Tamarack S78E 24.05' (S1, NBT)
7" Spruce S43W 30.75' (1/4S, NBT)	5" B. Spruce S15W 11.5' (S2, NBT)
7" Spruce N04W 28.75' (1/4S, NBT)	5" B. Spruce N71W 11.0' (S35, NBT)
All trees are blazed, scribed and painted. Measurements are to nail in side of tree, bearings are magnetic.	All trees are blazed, scribed and painted. Measurements are to nail in side of tree, bearings are magnetic.



Signed by Paul R. Bressette

Date

Surveyor's Michigan License No. 37270

For the Michigan Department of Natural Resources - Forest Management Division