DEC 1 8 2837

٠٠٠ أنعياً الله

COMPERTY

97 NOV 24 AM 10: 26

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	LINDA M. TWITCHELL
EATON COUNTY Located In: Corner Code #	REGISTER OF DEEDS EATON COUNTY. MICH.
CARMEL TOWNSHIP	
1. Public Land Survey T_2N_R_5WK-9	CDDU.
TR	Liber 3 pg. 838
TR	6.11 2 000
2. Property Controlling S T B	liber 3 pg. 838
in Section S T R	(0
3.Miscellaneous	Register of Deeds Stamp & File Number
Troperty in Sec. S I	register of Deeds Startly & the Number
4. Lot No, Recorded Plat	
5. Private Claims	A B C D E F G H I J K L M
	2 - 5 - 4 - 3 - 2 - 1
I DAVID I CLIEFORD in a field surrouses CERTEMBER 12 10.07	3
I, <u>DAVID L. CLIFFORD</u> , in a field survey on <u>SEPTEMBER 12</u> , 19 <u>97</u> do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points	4 - 7 - 8 - 9 - 10 - 11 - 12 -
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior,	5
Bureau of Land Management or by a decree of a Court of Law and /or that the corner points	6 18 17 16 15 14 13 1
mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,	7
recovered, found as expressed below:	8 19 20 21 22 23 24
NOTE: Not more than 2 corners, all in the same town and range, may be recorded	9
on this certificate.	10 30 29 20 27 26 25
	11
	12 -31 -32 -33 -34 -35 -36
A. Description of original monument and accessories and/or subsequent restoration: 1. SYLVESTER SYBLEY D.S. SET ORIGINAL CORNER IN DECEMBER 1825: BEECH 6" \$17°E, 11 LKS; W.OAK, 11", N76½°W, 2 LKS. 2. EATON COUNTY ROAD COMMISSION GRID MAP: ANCHOR POST S. 30.0' 3. ROBERT REED RLS 19004 USED CORNER IN AN ACT 132 SURVEY RECORDED IN LIB. CERTIFICATE IN LIBER 2 PAGE 415 IN JUNE 1977 AS A SET 1/2" BAR & CAP AT REFER PROPORTIONATE MEASUREMENT AND CORROBATIVE AND CORRELATIVE EVIDENCE: 197.96'; PK IN 6" SQUARE RAILROAD FENCE END POST, S.E., 42.08'; PK IN RAILROAD SECTION CORNER-10" TWIST SPIKE WITH CAP- WEST 4.81'	RENCE CORNER 4.81' EAST OF CORNER BY N.E. CORNER BASE SIGNAL TOWER, SW,
B. Description of corner evidence found and/or method applied in restoring or reestablishing SEARCHED AT APPARENT LOCATION OF CORNER AND FOUND 1/2" BAR & CAP #1900 AND 2' SOUTH OF CENTERLINE KALAMO HIGHWAY. RAILROAD CROSSING HAS BEEN & BY REED AT CORNER IS GONE. ACCEPTED REED'S POSITION AS PERPETUATION OF COROAD COMMISSION INFORMATION. SET 3/4" BAR AND PA 345 CAP 4.81' WEST OF FOR BOX. MEASURED EAST 2650.66' TO L-9 AND SOUTH 2679.22' TO K-10. C. Description of monument for corner and accessories established to perpetuate locating.	4, 4.8' EAST OF A FENCE LINE TO SOUTH UPGRADED AND SPIRAL SPIKE CALLED FOR DRNER BECAUSE OF AGREEMENT WITH UND 1/2" BAR & CAP AND SET MONUMENT
K-9 T2N, R5W	•
3/4' BAR & ORANGE PLASTIC CAP IMPRINTED PA 345 PS 25837 2.0' SOUTH OF CENTE TO SOUTH	ERLINE KALAMO HIGHWAY ON FENCE LINE
FOUND PK NAIL WEST SIDE TELEGRAPH POLE, 15° NAZ, 67.88'	OF MICH.
USC&GS BENCH MARK, 80° NAZ, 103.30°	DAVID L. CLIFFORD
N.E. CORNER BASE ELECTRICAL TRANSMISSION TOWER, 195° NAZ, 97.93' N.W. BOLT IN CONCRETE BASE RAILROAD SIGNAL LIGHT, 230° NAZ, 95.20'	DAVID L.
N.E. BOLT IN CONCRETE BASE RAILROAD SIGNAL LIGHT, 250° NAZ, 105.66'	CLIFFORD A LAND A LAND
1/2" BAR & CAP #19004 (REFERENCE CORNER), 90° NAZ, 4.81' EAST RAIL OF RAILROAD TRACKS, 270° NAZ, 3.7'	SURVEYOR
1	25837
	The second secon
Signed by David 2. Clifford	WWW. Warren of the same of the
Surveyor's Michigan License No. 25837	Date_OCTOBER 13, 1997
FORM APPRO	IVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
	REVISED MAY 14,1975 REVISED JAN., 1983
	REVISED OCT., 1995

P.A. 345 EATON COUNTY
PEER APPROVED 10/14/97 VM