## SURVEY & REMONUMENTATION

## EA (ON COUNTY REMONUMENTATION

FILED

JAN 1 1 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Copy

	t timig rv	equitement of 7 or 7	.,	00.1	nicja pr	n. : =
SECTION				1 00	NUG 22 PM	2: 45
For Corners in EATON	Located In:	Corner Code #		LINE	DA M. TWITCH	JC1 1
(county)		•		RE	GISTER OF DEI	EDS
1. Public Land Survey CORNER COMMON TO SECTIONS 7 & 18,	T 2N R 6W T R R	B-5		A.3	TON COUNTY, M	иин.
KALAMO TOWNSHIP	T R			LIBER	À PALE	1/16
2. Property Controlling Sin Section S	TR TR		_	Register of Deeds		
3. Miscellaneous S	T R			ABCDI	EFGHI	JKLM
	•			1 7 7		
	Plat			2 - 6 - 5 - 3	- <del>1</del> - 3	
5. Private Claims			<u></u>	4 7 - 8 -	9 10	11 12-
1, Brian Reynolds, in a field survey o	n 9 AUGUST, 2000 do l	hereby certify that under	requirements	5		
of P.A. 74, Michigan P.A. of 1970, the conformance with regulations and rule	corner points mentione	ed in lines 1 and 2 above	were in Survey	6 18 17 -	16 - 15 -	1413
instructions of the United States Department	artment of the Interior, E	lureau of Land Managem	ent or by	7	21-22-	23-24
a decree of a Court of Law and/or tha	it the corner points ment	tioned in lines 3, 4, and 5	above	9   10   20	<del>                                     </del>	
were in conformance with the rules of of a Court of Law; established, re-est	the Michigan Board of	Land Surveyors or by a L re-monumented recover	ed found	10 -30 29	2827-	2625-
as expressed below.				11	00 34	35 36
NOTE: Not more than 2 corners, all	in the same town and	range, may be recorde	d on this	12 31 32	33 - 34	33 30
certificate.  A. Description of original monumers	ent and accessories a	and/or subsequent rest	oration:		410 VI 05	
1. GENERAL LAND OFFICE DEP	UTY SURVEYOR MUS	GROVE EVANS, 1826, *	BEECH 18 51	4W 35 Do. 10 N27 NAME OR DATE.	1/2 W 25	
3 COUNTY ROAD COMMISSION	TRANSCRIPTION OF	GENERAL LAND OFFIC	E SURVEY, MA	RGINAL NOTE "1920	DEC. 23 E. A. W	ELLS FOUND
PILE OF STONES (LARGE CE	NTER ONE) REPLACE	D WITH STAKE INSIDE	OF 5" TILE AND	PLACED STONE AR	OUND IT	
ANCHOR POST NORTH 23.6 4. COUNTY ROAD COMMISSION	ANCHOR POST SO	OUTH 29.1 GENERAL LAND OFFIC	E SURVEY. MA	RGINAL NOTE "1/4 C	ORNER COMMO	N TO 7 & 18
4. COUNTY ROAD COMMISSION 3/4" BOLT SOUTH 3	4.20' COR. FENCE PC	OST (CAP & NAIL)	S52°E 56.79'	TELE. POLE (CAP & 1	NAIL)	
N33°W 36.84' TELE. POLE (C	AP & NAIL)	M.S.D.H. 1954	40000 DATED 2	MAMOOS AND DECOR	DED 2/42/4992 IA	ITIRER 3 PAGE
5. LAND CORNER RECORDATIO 186, (PART "B") FOUND COP	ON CERTIFICATE BY K RNER AS CALLED FOI	(AY DON FLUKE, P.S. # R IN MDOT PLANS DAT	18988, DATED 3 ED 1959, PROJI	ECT 23-36, BOAT SPI	KE IN MONUMEN	T BOX
(PART "C") EOAT SPIKI	E IN MON. BOX N35	E-87.93-NE COR HSE.#	11451*****SOUT	H-59.48-POWER POL	E****	
N04W-59.22-R/W MARKER(TO	P CENT.)**** N19W-62	91-TEL, POLE	#29243 DATE	n sidi1995 AND RECC	RDFD 5/5/1995 II	N LIBER 3. PAGE
6. LAND CORNER RECORDATION 590, (PART "A") RECITES SA			RT "B") FOUNI	D BOAT SPIKE IN MO	NUMENT BOX OF	CENTERLINE OF
M-79. FIT HIGHWAY R.O.W. N	MAP AND STATIONING	i. (PART "C")		MONUMENT BOX	ma mai	
CONC. R/W MARKER (CENTE		ELE. PED. (CENTERLIN	IE TOP) N24°W	61.28° U. PULE 5	59.50	
NW COR HSE.#11451 S46°W 7. LAND CORNER RECORDATION	ON CERTIFICATE: BY	WALLACE E. GLAZA, F	.s. #31592, 2-S	EPT-99 (L.4, P. 53) "F	OUND BOAT SPI	KEIN
MONUMENT BOX" FOUND N	IAIL & TAG IN W. SIDE	P. POLE S03°W 59.51'	FC	OUND NAIL & TAG IN	SW SIDE 10" ELN	Λ S61°E 46.71'
NW CORNER HOUSE No. 114 8. ACT 132 SURVEY: BY LARRY	51 S43°W 107.46' C/ Y BRYAN P.S. #25832	'L MBT BOX N27°W 61.1 . 14-MARCH-97 (L.6. P.F	13' IN C/L E-W E 2.770-772) FND	BOAT SPIKE IN MON	BOX IN C/L M-7	9 ON FENCE
LINES NORTH & SOUTH FI	VD CONCRETE RIGHT	OF WAY MARKER S13	°W 61.50'	FND CONCRETE RIG	HT OF WAY MAR	RKER N01°E 59.22'
FND NORTHWEST CORNER I	HOUSE #11451 S49°W		AIL & TAG #189	88 IN WEST SIDE PO	WER POLE S10°	N 59.55'
SET NAIL & TAG IN WEST SIZE  B. Description of corner evidence	e found and/or metho	d applied in restoring	or reestablishin	ng corner:		
FOUND BOAT SPIKE IN MONUME	NT BOX ON CENTERL	INE OF M-79 AND MOS	T WITNESSES I	BY FLUKE, CRANE, G	LAZA & BRYAN.	MEASUREMENTS
TO ADJACENT GRID CORNERS E BOAT SPIKE AS PROPER PERPE	AST & WEST ARE CO	NSISTENT WITH DISTA POSITION, REPLACE	NCES RECITED D FOUND BOAT	SPIKE WITH STAND	ARD EATON COL	INTY
REMONUMENTATION MONUMENT	T IN MONUMENT BOX					
C. Description of monument for C SET STANDARD EATON COU	corner and accessori	es established to perperation monument	etuate locating	the position of the cannot with all LIMINE	orner: IM CAP.	
TOP CENTER OF A CONCRET	E RIGHT OF WAY N	MARKER S13°W 61.55	ON NOR	RTHWEST CORNER	R, HOUSE #114	51 S49°W 107,41'
NORTHEAST CORNER, HOUS	E #11451 S30°W 87	7.96' IN LINE W.	ITH FENCE NO		56'	Market Of HICH
FOUND NAIL & METAL TAG (FOUND NAIL & METAL TAG (	NO IDENTIFICATION	I) IN THE WEST SIDE	OF A 10" MA	PLE S35°E 46.70'	g fter	BRIAN ,
CORNER IS ON EAST-WEST (	CENTERLINE (M-79)					*/ REYNOLD'S
A-5 LIES S88°32'32"E 3051.86	B-6 LIES \$05°4	46'39"E 2673.67'	A		02 - <b>3</b>	SURVE FOR
	7		4	.)( )(-)	7000	NO NO
Signed by	NIO 24COO		Date_/	CC C > 1 /6	ADDOCUMENTS	mod AN TOMOZETOWAN
Surveyor's Michigan Licen'se	No 31602		FORM APPROVI	ED BY MICHIGAN STATE BOX	HALD OF LAND SURVEY	ORS. JAN. 28, 1974