

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Located In Corner Code #
Emmet (County)

1. Public Land Survey T 36 N R 6 W K-3
T
2. Property Controlling in Section S 11 T 36 N R 6 W 9
S T R
3. Miscellaneous Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 6, 2000 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-3 GLO John Mullet, D.S. 1840
Set post corner Sections 1,2,11, and 12
Wit: 10" Birch S62°E 11 links
9" Elm N65°W 13 links

9- This corner position was not established during the original government survey.

Liber 1, Page 294, Danny Bongiovanni, RLS #24586
Set ¾" pipe in road intersection
Wit: Power Pole S14°E 58.85'
16" Maple N34°W 75.53'
8" Maple S44°W 37.57'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-3 Found ¾" pipe

9- Established the Northwest corner of the Northeast quarter of Southeast quarter of section 11 per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3 Found ¾" pipe
Wit: * 8" Spruce N54°E 52.16'
* Power Pole S15°E 58.84'
12" White Pine N30°W 62.87'
12" Maple Clump S46°W 37.81'
* Old witness by others

9- Set 5/8" x 32 rerod with PS cap #33981
Wit: 3" Cherry N61°W 32.11'
5" White Pine N77°E 32.29'
8" White Pine S51°E 47.00'
3" Cherry S29°W 80.89'
North/South Fence West 40.5'±
Carsonite post set 1'± North

Signed by: Carl T Kiiskila
Surveyor's Michigan License No.: 33981

Date: 8-1-00

