

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Emmet
(County)

Located In

Corner Code #

1. Public Land Survey	T		R		
	T		R		
2. Property Controlling in Section	S 36	T 37N	R 5W	8	
	S 36	T 37N	R 5W	9	
3. Miscellaneous Property in Section	S	T	R		
	S	T	R		

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on May 12, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

8 - CW 1/16 Cor. Section 36, T37N, R5W

9 - CE 1/16 Cor., Section 36, T37N, R5W

None

None

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

8 - CW 1/16 Cor. Section 36, T37N, R5W

9 - CE 1/16 Cor., Section 36, T37N, R5W

Set stamped 2" alum. cap on 5/8"x34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner.

Set stamped 2" alum. cap on 5/8"x34" rebar per standard BLM procedure. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

8 - CW 1/16 Cor. Section 36, T37N, R5W

9 - CE 1/16 Cor., Section 36, T37N, R5W

Stamped 2" Aluminum cap on 5/8"x34" rebar
Witnesses:

N37°E 22.39' to set N&T on E side 18" Beech
S64°E 16.64' to set N&T on S side 10" S.Maple
S56°W 34.02' to set N&T on NW side 11" Cherry
N53°W 13.68' to set N&T on S side 9" Beech
West 95' to N-S fence remains and postings.
South 37' to E-W fence remains.
Set Blue Carsonite Post w/loc. tag 1' North

Stamped 2" Aluminum cap on 5/8"x34" rebar
Witnesses:

N04°E 22.70' to set N&T on E side 9" S.Maple
S13°W 20.17' to set N&T on N side 4" S.Maple
S44°W 5.01' to set N&T on E side 6" S.Maple
N77°W 17.29' to set N&T on N side 8" S.Maple
Set Blue Carsonite Post w/loc. tag 1' North

Carl T. Kiiskila

Surveyor's Michigan License No.:

33981

7-15-09

