## SURVEY & REMONUMENTATION

MAR 23 2000

SECTION

## LAND CORNER RECORDATION CERTIFICATE EC 21 2 46 PM 199

Mil Parke

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	GENESEE GOUNTY REGISTER OF THE DS						
Genesee Located In:Argentine Corner Code # G-2 (County)			143			•	5
1. Public Land Survey  T 5N R 5E G-2  T R  2. Property Controlling S T R in Section S T R 3. Miscellaneous S T R Property in Sec. S T R	filed 9 Register	of Deeds	Stamp	& File	Numbe	er 	
4. Lot No, Recorded Plat		1 A B C	5 D E	4 <b>4</b>	Э H \	J К 2	1
		4 7	8	9	10	11	12
I, <u>Gilbert G. Bonno, P.S.</u> , in a field survey on <u>November 17</u> 19 99 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the			17	16	15	14	13
current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:		7 8 19	20	21	22	23	24
		0 30	29	28	27	26	25
NOTE: Not more than 2 corners, all in the same town and range, may be ron this certificate.	l condea	2 31	32	33	34	35	36
A. Description of original monument and accessories and/or subsection 1823, GLO - Harvey Parke DS; set post and two accessories, measured 1890, County Surveyor, Moses Middleton CS, Stake and stone, one new to F-2 1991, Mary Barnwell Dwyer field notes, no description of monument give	sequent resto d G-2 to G-1 w accessory, me	ration: easured G				3-3 and	G-2

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1999 Remon - found 1" pipe with cap #33971 (Mart Barnwell-Dwyler) remnants of old fence running east-west and south

In 1823, DS Harvey Parke set a wood post for corner G-2 with two accessories being noted, neither of which exist today. He also had a measurement G-2 to G-1 of 42.26 chains (2789.16 feet), 1999 Remon G-2 to G-1 measures 2805.39 feet. In 1890, Moses Middleton indicates a stake and stone as the objects in place for the corner G-2 and one accessory which no longer exists. He indicates three measurements G-3 to G-2 40.215 chains (2654.19 feet), 1999 remon. G-3 to G-2, 2655.28 (1.09 feet longer); G-2 to G-1 42.56 chains (2808.96 feet), 1999 remon. G-2 to G-1, 2805.39 feet (3.57 feet short of 1890 record); G-2 to F-2 40.34 chains (2662.44 feet), no 1999 remon. measurement. In 1991, Mary Barnwell-Dwyer P.S.#33971 set a 1" pipe with cap #33971 at single proportionate measure and on line between corners G-3 to G-1. From the 1823 GLO survey record measurement to the 1991 measurement, G-3 to G-2 1991 proportionate measure = 2655.39 feet (1890 C.S. measurement G-3 to G-2 was 2654.19 feet; 1.2 feet difference). The 1999 remon. measurement G-3 to G-2 is 2655.28 feet (0.11feet difference from the 1991 survey G-3 to G-1). I accept the 1" pipe set by Mary Barnwell-Dwyler at single proportionate measure and on a straight line between corners G-3 and G-1as the careful and faithful perpetuation of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

N70°W 11.17' Found spike in north face 10" Oak S30°E 16.33' Found spike in Southwest face 14" Oak S60°E 25.74' Found spike in South face 16" Oak S30°W 5.10' Found spike in East face 36" Oak N85°E 20.57' Set PK nail and Genesee County witness tag in South face of 4" Ash Ratified by the Genesee County Peer Group
November 17, 1999
I set the Standard Bernsten Monument SS-A-5-BR-30
(3 1/4" D. Brass cap stamped "Genesee County
Remonumentation Corner 32332, 1999") with 30" x 2 3/8"
O.D. stainless steel tube set in monument box.

Ratified by Peer Group in accordance with P.A. 345, 1990
Co. Rep. Coul also
Date 11-17-99

Signed by Jelland 4- Bonno Surveyor's Michigan License No. #32332



Date / C/ ( ) ( ( )

PROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 197

EVISED MAY 14, 197

ADAPTED FOR WORD PROCESSING MARCH, 1