

Register's Office }  
Gogebic County } ss.  
**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic  
(County)

Located In:

Corner Code ##

Received for record the

3<sup>RD</sup> day of FEBRUARY

A. D. 1993 at 10:35 o'clock

9 m., and recorded in

Liber 4 of CORNER

on page 218

Richard J. Brown  
Register of Deeds

Register of Deeds Stamp & File Number

1. Public Land Survey

44/  
T 43N R 38W

AB-1e

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. \_\_\_\_\_, Recorded Plat

5. Private Claims

**PEER GROUP**

**Approved**

Richard L. Drach

1/20/94

I, Gary L. Pisoni, in a field survey on November 12, 19 92,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Austin Burt, U.S. Deputy Surveyor on June 8, 1847.

Original corner: Tamarack Post

Original bearing tree:

Tamarack

8"

N 13° 30' E

22 links (14.52 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence found. Corner restored on line between the Northeast  
and Northwest Section corners of Section 6 on the East shore of Lac Vieux Desert.  
Said Meander Corner located 14 feet from waters edge.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 3/4" outside diameter by 12 feet long aluminum rod  
monument with a 3" cast aluminum cap, stamped to read; T44N R38W; M.C.; S-31; S-6;  
T43N; 1992; R.L.S. 27457 from which established the following new blazed and  
scribed bearing trees: (all measurements taken to a nail in side of tree)

Tamarack	6"	N 50° E	42.36 feet
Tamarack	11"	S 23° E	29.23 feet
Steel Sign Post		North	0.95 feet
Steel Sign Post		East	0.95 feet

Signed by Gary L. Pisoni

Date

1/28/93

Surveyor's Michigan License No. 27457

U.S.F.S. A-2,3

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

