

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic  
(County)

Located In:

Corner Code -##

1. Public Land Survey

T 43N R 38W E-2,3

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

PEER GROUP

Approved

5. Private Claims

Richard L. Pisoni

1/20/94

I, Gary L. Pisoni, in a field survey on November 12, 19 92,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Zelotes B. Searls on July 30, 1851.

Original corner: Cedar 10" for Meander Corner

Original bearing tree:

Cedar

8"

N 20°W

4 links (2.64 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence found. Meander corner restored on the North bank of  
Lac Vieux Desert on line between the Northeast Section corner of Section 5 and  
the North Meander corner between Sections 8 and 9 located on the North shore of  
Desolation Point.

Meander corner located 22 feet from waters edge.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 3/4" outside diameter by 3 feet long aluminum rod  
monument with a 3" cast aluminum cap, stamped to read: T43N, R38W; S-5; S-4; M.C.;  
1992 R.L.S. 27457 from which I established the following new blazed and scribed  
bearing trees: (all measurements taken to a nail in side of tree)

Cedar (double)	3"	N 60°W	6.51 feet
Cedar	10"	East	36.76 feet
Cedar	8"	S 53°E	25.28 feet
Steel Sign Post		N 45°E	0.75 feet

Register's Office }  
Gogebic County } ss.

Received for record the

3<sup>RD</sup> day of FEBRUARY

A. D. 19 93 at 10:35 o'clock

A m., and recorded in

Liber 4 of CORNERS

on page 223.

Richard L. Brown  
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Signed by Gary L. Pisoni

Date

1/28/93

Surveyor's Michigan License No. 27457

U.S.F.S. C,D-9

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

