

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }  
Gogebic County } ss.

Received for record the

3<sup>RD</sup> day of FEBRUARY

A. D. 1993 at 10:35 o'clock

A m., and recorded in

Liber 4 of CORNERS

on page 224

Richard L. Brown/m

Register of Deeds

Register of Deeds Stamp & File Number

For corners in  
Gogebic  
(County)

Located In:

Corner Code: //

1. Public Land Survey

T 43N R 38W

E-3,4

T R

T R

T R

S T R

S T R

S T R

S T R

2. Property Controlling  
in Section

3. Miscellaneous

Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

North Meander Corner Sections 8 and 9

I, Gary L. Pisoni, in a field survey on November 12, 1992, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Zelotes B. Searls on July 30, 1851.

Original corner: Wood Post

Original bearing tree:

Tamarack

6"

South

19 links (12.54 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence found.

Corner position marked by a 4"x4" concrete monument with iron pin in center of monument.

Monument is part of an unrecorded plat in section 8 of Desolation Point. Monument

believed to be set in the 1950's.

Monument located 19 feet North of centerline of gravel access road to Desolation Point.

PEER GROUP APPROVED

Richard L. Brown

1/20/94

COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the above described monument I established the following new corner accessories.

Steel Sign Post

North

0.9 feet

Steel Sign Post

West

0.8 feet

Signed by Gary L. Pisoni

Date

1/28/93

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

