

SURVEY & REMONUMENTATION

NOV 12 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

Received for record the
27TH day of OCTOBER
A. D. 1997 at 11:15 o'clock
A m., and recorded in
Lib. 6 of CORNERS
on page 255
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

For corners in

Gogebic
(County)

Located in:

Corner Code #

1. Public Land Survey

T43N R 38W

DE 4-5

T R

#011

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Mile Corner #12 1/2 + 1069.6, Michigan-----Wisconsin State Line

I, Gary L. Pisoni, in a field survey on June 27, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by William Burt in 1847.

Original bearing trees:

Hemlock	9"	N 82°E	15 links (9.90 feet)
Cedar	12"	S 43°W	23 links (15.18 feet)

PEER GROUP APPROVED
Richard L. Drach 10/10/97
COUNTY REPRESENTATIVE

Corner restored in 1928 by Earl G. Harrington on line between Mile Corner #12 1/2 and to Meander Corner 12 1/2 + 1076.9 feet on the East shore of Lac Vieux Desert.

White Birch	6"	N 78°40'E	18.5 links (12.2 feet)
Hemlock	24"	S 21°30'W	75 links (49.5 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Recovered the 1928 standard brass capped concrete monument as described in Harrington's notes as being at 12 1/2 + 1069.6 feet. Harrington found the Northeast Hemlock B.T. with scribing visible, but Meander corner falls in lake. He reset new Meander corner on high ground and on line between Burt's corners.

No evidence of William Burt's B.T.s found. The 1928 White Birch B.T. is now a 10" birch dead snag and the 1928 Hemlock is a decayed stump.

Corner Record Research on file with County Representative

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the above described concrete monument, I established the following:

Sugar Maple	4"	N 65°E	33.80 feet
Sugar Maple	4"	S 72°E	17.20 feet
Balsam	7"	S 32°E	13.23 feet
White Birch	11"	S 07°W	9.17 feet
Steel sign post		S 72°E	4.1 feet



97-11
Signed by Gary L. Pisoni

Date 7-15-97

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1976
REVISED JAN., 1983
REVISED OCT., 1995