

# SURVEY & REMONUMENTATION

NOV 12 1997

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic  
(County)

Located In:

Corner Code #

1. Public Land Survey

T43N R 38W

EF 4-5

T R

Other

T R

# 012

T R

T R

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

Register's Office } ss.  
Gogebic County

Received for record the  
27<sup>th</sup> day of OCTOBER  
A. D. 19 97 at 11:15 o'clock  
A m., and recorded in  
Lib. 6 of CORNERS  
on page 256  
Ramona Collins, Deputy  
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Mile Corner #12 1/2, Michigan-----Wisconsin State Line

I, Gary L. Pisoni, in a field survey on June 27, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by William Burt in 1847.

Original bearing trees:

Sugar Maple	10"	N 32°W	50 links (33 feet)
Sugar Maple	24"	S 35°E	12 links (7.92 feet)

Corner restored in 1928 by Earl G. Harrington by proportional measurement methods. No original B.T.s found. He set a standard brass capped concrete monument and two new B.T.s.

Elm	8"	S 83°45'W	41.8 links (27.6 feet)
Maple	18"	N 55°E	29.2 links (19.3 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Recovered the 1928 standard brass capped concrete monument as described in Harrington's notes. The 1928 Elm B.T. is now a 15" Elm dead snag and the 1928 Maple is a live 26" Maple with grown over blazes.

No evidence remains of the 1847 B.T.s.

Corner Record Research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

From the above described concrete monument, I established the following:

Sugar Maple	12"	N 40°W	44.52 feet
Basswood	12"	N 74°E	24.89 feet
Sugar Maple	8"	S 26°E	18.47 feet
Sugar Maple	7"	S 31°W	55.18 feet
Steel sign post		N 59°W	0.82 feet

97-10

Signed by Gary L. Pisoni

Date 7-15-97

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995

PEER GROUP APPROVED

Richard L. Dralun 10/16/97  
COUNTY REPRESENTATIVE

