

OCT 03 1996

## TRANSMISSION

For corners in \_\_\_\_\_ Gogebic  
(County)

Located In: Corner Code #

1. Public Land Survey	Sec. 3	T	43N	R	39W	G-1-2
		T		R		
		T		R		
		T		R		
		T		R		
2. Property Controlling in Section	S	T		R		
	S	T		R		
3. Miscellaneous Property in Section	S	T		R		
	S	T		R		

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Meander corner to Sections 3 &amp; 4, T43N, R39W

I, John R. Garske, in a field survey on February 26, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

Original corner set by Wells Burt, D.S. on August 24, 1851, 3.56 chains south of post on town line from which:  
A tamarack 6" - N88°W - 44 links and a W. pine 10" - N11°E - 86 links.

- 1938 - Corner set by James Jezek, Surveyor and Chas. Walker, Engineer, as part of Gunderson's Plat on Crystal Lake, they set a concrete monument.
- 1962 - Corner recovered by Donald Lappala, RLS, and shown on a U.S.F.S. Plat of Survey as concrete monument.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

I recovered the concrete monument noted above by Lappala and shown on the Gunderson Plat. The M.C. location checks with GLO distances and other plat corners found in the area.

(Research on File)

PEER GROUP APPROVED  
Richard L. Deahn 3/27/96  
COUNTY REPRESENTATIVE

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

**Found 4" square concrete monument at the meander corner location from which I established the following:**

24" J. pine - N61°W - 12.04 feet  
12" Aspen - N40°E - 13.28 feet  
14" Aspen - N73°E - 25.33 feet  
Steel sign rail - N05°E - 1.07 feet



Signed by John F. Cooke  
Surveyor's Michigan License No. 28410

Date 3/27/80 CO LAND SUR  
FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN. 1983