

DEC 15 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T_43N R_39W

1. J 2-3

T R

T R

T R

T R

T B

T R

T R

2. Property Controlling in Section

3. Miscellaneous

Property in Sec.

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Mile Corner # 47½ +1951.1 , Wisc.- Mich. State Line, T43N-R39W

I, Gary L. Pisoni, in a field survey on October 16, 1998 do hereby
state

that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William A. Burt, U.S. Deputy Surveyor in 1847

The State boundary line as originally surveyed was retraced and re-established under the direction of the Michigan-Wisconsin Boundary Commission, by Earl G. Harrington, Cadastral Engineer in 1928-1929. Mile Corner No. $47\frac{1}{2} + 1951.1$ which is a concrete monument 26" long, 6" square at the top, 7 1/2" square at the base, fitted with a metal tablet marked for Mile Corner No. $47\frac{1}{2} + 1951.1$. No evidence of the original corner or bearing trees found. Monument set on East shore of channel of Birch Lake.

1928 Bearing Trees: None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

On 10/16/98, found the monument as described above, flush with ground surface.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

White Pine	7"	S 82° W	19.06 feet
Red Maple	6"	S 48° W	9.14 feet
Red Maple	6"	S 47° E	37.41 feet
Steel sign post	6'	South	1.2 feet

98-G6

Signed by Harry L. Person Date October 24, 1998

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN 18 1972

Register's Office } ss.
Begebic County }

Received for record the
4TH day of NOVEMBER
A. D. 19 98 at 3:20 o'clock
P m., and recorded in
Liber 7 of CORNERS
on page 78.
Ramona Collins, Deput
Register of Deeds

Register of Deeds Stamp & File Number[illegible]

DEER GROUP APPROVED
Richard L. Dredin 10/27/98
COUNTY DEER GROUP

