

DEC 15 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Gogebic</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>43N</u> R <u>39W</u>	<u>1J2-3</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u>006</u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

Register's Office } ss.
Gogebic County }

Received for record the
4TH day of NOVEMBER
A. D. 1998 at 3:20 o'clock
P m., and recorded in
Liber 7 of CORNERS
on page 79.
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Mile Corner # 47 1/2 + 1521.6, Wisc.- Mich. State Line, T43N-R39W

I, Gary L. Pisoni, in a field survey on October 16, 1998 do hereby
state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as
required in the current manual of survey instructions of the United States Department of
the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that
the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules
of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William A. Burt, U.S. Deputy Surveyor in 1847

The State boundary line as originally surveyed was retraced and re-established under the direction of the Michigan-Wisconsin Boundary
Commission, by Earl G. Harrington, Cadastral Engineer in 1928-1929. Mile Corner No. 47 1/2 + 1521.6 which is a concrete monument 26"
long, 6" square at the top, 7 1/2" square at the base, fitted with a metal tablet marked for Mile Corner No. 47 1/2 + 1521.6. No evidence
of the original corner or bearing trees found. Monument set on West shore of channel on Birch Lake.

1928 Bearing Trees: None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

On 10/16/98, found the monument as described above, 6" above ground surface.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees: (All measurements taken to a nail in side of tree)

Red Pine	14"	West	6.83 feet
White Pine	10"	N 14° W	26.66 feet

No blazing or scribing on the following bearing trees: (All measurements taken to a nail in side of tree)

White Pine	10"	N 83° E	6.05 feet
White Pine	13"	N 49° W	39.63 feet
Fiberglass sign post		S 55° W	1.33 feet

98-G7

Signed by Gary L. Pisoni
Surveyor's Michigan License No. 27457

Date October 24, 1998

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1977

PEER GROUP APPROVAL
Richard L. Deahn 10/27/98
COUNTY REPRESENTATIVE

