

DEC 15 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic
(County)

Located In:

Corner Code #

1. Public Land Survey

T 43N R 39W

L. 2-3

T R

T _____ R _____

T _____ R _____

T_____R_____

T_____ R_____

T_____R_____

T R

2. Property Controlling in Section

3. Miscellaneous

Property in Sec.

4. Lot No. _____, Recorded Plat _____

5. Private Claims

Closing Corner between Sections 3 and 2, T43N, R39W, Wisc-Mich State Line

I, Gary L. Pisoni, in a field survey on October 16, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Wells Burt, U.S. Deputy Surveyor in 1851.

Original Corner: White Birch 6" dia. for closing corner

Found a 2" diameter iron pipe located on the Michigan-Wisconsin State Line

marking the closing corner position, 24" above ground surface with a 3" diameter brass tablet

stamped as follows: T43N, R39W, S-3, S-2, Mich.-Wisc.

Iron pipe set by unknown person(s) and used for many surveys in Sections 2 and 3.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.'s found.

On 10/16/98, found the monument as described above.

Corner record research on file with County Representative.

PEER GROUP APPROVAL

Richard L. W. W. W. 10/27/98
COUNTY

COUSIN **REARER**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

No blazing or scribing on the following bearing trees: (All measurements taken to a nail in side of tree)

Red Pine 15" N 61° W 26.11 feet

White Spruce	12"	N 04° W	20.11 feet
			8.63 feet

Red Pine	16"	S 85° E	18.27 feet
----------	-----	---------	------------

98-G8
Signed by *Tary L. Lison* Date October 24, 1998

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 23, 1971
 REVISION, MAY 1, 1975
 REVISION, JAN., 1983
 REVISION, OCT., 1994

