

SURVEY  
RECORDATION

DEC 15 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office  
Gogebic County ss.

For corners in

Gogebic  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 44N R 39W D-E.13 009

T 43N R 39W D-E.1 009

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Received for record the  
4<sup>th</sup> day of NOVEMBER  
A. D. 1998 at 3:20 o'clock  
P. m., and recorded in  
Liber 7 of CORNERS

on page 82  
Ramona Collins, Deputy  
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Closing Corner between Sections 32, T44N, R39W, and  
Section 5, T43N, R39W, Wisc-Mich State Line

I, Gary L. Pisoni, in a field survey on October 16, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by John Burt, U.S. Deputy Surveyor in 1847.

Original Corner: White Birch post

Original Bearing Trees:

Yellow Pine 10" S 62° E 54 links

Yellow Pine 18" N 63° W 64 links

On 10/10/67, Donald D. Lappala RLS with the U.S. Forest Service restored the corner position from the original two bearing trees and set a 2" diameter x 5' long galvanized iron pipe 18" above ground surface with a 3" diameter brass tablet stamped as follows: T44N, R39W, S-32, S-5, State boundary, T43N, 1967, RLS 12585 from which he established the following blazed and scribed bearing trees:

1967 Bearing Trees:

Tamarack 10" S 88° E 41.8 feet

Tamarack 10" S 08° W 25.7 feet

White Pine 16" S 85° W 46.8 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found one of the original bearing tree stumps, Yellow Pine 18" N 63° W 64 links.

On 10/16/98, found the monument as described above and the following bearing objects: (All measurement taken to a nail in side of tree):

White Pine 22" S 85° W 46.56 feet

Tamarack 13" S 09° W 25.56 feet

Tamarack 11" S 88° E 41.98 feet

Wood sign post 4"x4" S 68° E 2.3 feet

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set the following bearing object:

Steel sign post

North

0.7 feet

98-G10

Signed by Gary L. Pisoni

Date October 24, 1998

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 24, 1971

