

SEP 08 1998

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Gogebic (County)

Located in:

Corner Code ~~##~~

- | | | | |
|---------------------------------------|--------------|--------------|------------|
| 1. Public Land Survey | T <u>44N</u> | R <u>39W</u> | <u>J-9</u> |
| | T _____ | R _____ | _____ |
| | T _____ | R _____ | _____ |
| | T _____ | R _____ | _____ |
| 2. Property Controlling
in Section | S _____ | T _____ | R _____ |
| | S _____ | T _____ | R _____ |
| 3. Miscellaneous
Property in Sec. | S _____ | T _____ | R _____ |
| | S _____ | T _____ | R _____ |

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

$\frac{1}{4}$ Corner 23 , 26; T.44 N., R.39 W.

Richard L. Drahn, in a field survey on December 10, 19 97, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Corner established by Wells Burt on 8/28/1851. Original B.T.s --- Y. Pine
6" N.15 W. 26 links (17.16') --- Aspen 6" S.20 W. 37 links (24.42') ---

Corner re-established on 6/8/87 by Gary L. Pisoni (27457) by extension of the lines of the Curry Plat into the corner position. He set a 2" X 30" aluminum pipe with a 3¼" stamped alum. cap and the following references:

7" Balsam N.28 E. 7.61'

14"	Red Pine	N.62 W.	55.95'
-----	----------	---------	--------

6"	Red Pine	N.06 W.	13.87'
----	----------	---------	--------

6' Metal sign post East 1.18'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner recorded in Gogebic County records in Liber 3, Page 150 on 8/24/88.

Corner research on file with Gogebic County records.

Recovered Pisonis' monument as described and his B.T.s as follows:

8" Balsam N.23 E. 7.58'

15" Red Pine N.62 W. 55.95'

7" Red Pine N.08 W. 13.87'

6' Steel sign post N.85 E. 1.10'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

New bearing tree referenced:

5" Balsam N.83 E. 14.09'

PEER GROUP APPROVED

Richard L. Dean 12/19/97
COUNTY DEPUTY CLERK

Signed by Richard L. Drahn Date December 11, 1997

Surveyor's Michigan License No. 21564

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

USFS R-19

323

Register's Office } ss.
Gogebic County }

Received for record the
17TH day of MARCH

A. D. 1998 at 9:55 o'clock
A m., and recorded in

Liber 6 of CORNER
on page 323.

Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number