

DEC 15 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Googebic County }

For corners in

Googebic Located In: Corner Code #
(County)

1. Public Land Survey T 44N R 39W D-E.13 009
T 43N R 39W D-E.1 009

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Received for record the
4th day of November
A. D. 1998 at 3:40 o'clock
P. M., and recorded in
Liber 7 of CORNERS
on page 82
Ramona Collins, Deputy
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Closing Corner between Sections 32, T44N, R39W, and
Section 5, T43N, R39W, Wisc-Mich. State Line

I, Gary L. Pisoni, in a field survey on October 16, 1998 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as
required in the current manual of survey instructions of the United States Department of
the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the
corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of
the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by John Burt, U.S. Deputy Surveyor in 1847.

Original Corner: White Birch post
Original Bearing Trees:

Yellow Pine 10" S 62° E 54 links
Yellow Pine 18" N 63° W 64 links

On 10/10/67, Donald D. Lappala RLS with the U.S. Forest Service restored the corner position from the original two bearing
trees and set a 2" diameter x 5' long galvanized iron pipe 18" above ground surface with a 3" diameter brass tablet stamped
as follows: T44N, R39W, S-32, S-5, State boundary, T43N, 1967, RLS 12585 from which he established the following blazed
and scribed bearing trees:

1967 Bearing Trees:

Tamarack 10" S 88° E 41.8 feet
Tamarack 10" S 08° W 25.7 feet
White Pine 16" S 85° W 46.8 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found one of the original bearing tree stumps, Yellow Pine 18" N 63 W 64 links.

On 10/16/98, found the monument as described above and the following bearing objects: (All measurement taken
to a nail in side of tree):

White Pine 22" S 85° W 46.56 feet
Tamarack 13" S 09° W 25.56 feet
Tamarack 11" S 88° E 41.98 feet
Wood sign post 4"x4" S 68° E 2.3 feet

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set the following bearing object:
Steel sign post

North 0.7 feet

98-G10
Signed by Gary L. Pisoni Date October 24, 1998
Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN. 1983
REVISED OCT. 1985

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

DEED GROUP APPROVED

Richard L. Dial 10/21/98
COUNTY REPRESENTATIVE

