		Register's ()ffice se.		
For corners in		riling Kequi	irement of Act 74, Mich. P.A.	1970 Received for record the
	Gogebic (County)	Located In:	Corner Code ##	A. D. 19 94 at 1:20 o'clock
1.	. Public Land Survey	T 44N R 41W	B-C,5b	Liber 5 of Corners on page 24
	•	T R T R	010	Betty Large Deputy
2.	Property Controlling in Section	S T R S T R	RPD	Register of Deeds
3.	Miscellaneous Property in Sec.	S T R S T R	10 110 198	Register of Deeds Stamp & File Number
4. 5.	Lot No, R Private Claims	RECORDED PLANTING PROPERTY OF THE PROPERTY OF	V V Abhroaed	A B C D E F G H 1 J K L
do in cu Ma ab Co	hereby certify that under requires 1 and 2 above were in frent manual of survey instru- anagement or by a decree of a ove were in conformance with	conformance with regulations a ictions of the United States Depa Court of Law and/or that the corn in the rules of the Michigan Board	mber 30 19 93 Tof 1970, the corner points mentione indirection therefore as required in the intension of the Interior, Bureau of Lander points mentioned in lines 3, 4 and of Land Surveyors or by a Decree of monumented, recovered, found a	e d 7 18 17 16 15 14 13 15 15 14 15 15 15 15 15 15 15 15 15 15 15 15 15
		ners, all in the same town and range, may be recorded		10 -30 -29 -28 -27 -26 -25
	on this certificate.		•,,	12 31 32 33 34 35 36
Α.	Description of original m	nonument and accessories an	d/or subsequent restoration:	13
	Original Corner: Original Bearing	: Willow Corner Tree Tree:	2: dia.	Deputy Surveyor on July 12, 1852
	Cedar	5 "	S 35 E 7 links (4.	.62 feet)
		2		:
3.	Description of corner evi	idence found and/or method a	applied in restoring or reestablis	hing corner:
	No original corn measurement meth of Section 7.	ner evidence found. (nods on line between t	Corner restored by sing the Southwest and South	ple proportionate least Section corners
				•
				· · · · · · · · · · · · · · · · · · ·

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, I set a 2" diameter by 30" long split base aluminum pipe monument with a 3" cast aluminum cap, stamped to read: T44N, R4lW, W.C., M.C., S-7, S-18, N89 50'W, 100.09', 1992, RLS- 27457 from which I established the following

new blazed and scribed bearing trees: (all measurements taken to a nail in side of tree)

Hemlock 9" N 34 W 4.53 feet

Hemlock 12" N 17 E 35.59 feet

Red Maple 5" S 72 E 50.52 feet

Steel Sign Post S 86 W 0.99 feet

CARY L.

Surveyor's Michigan License No. 27457

Date 3-12-94

FORM APPROVED BY MICHIGAN STATE BURNE OF LAND SURVINOUS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

PISONI LAND SURVEYOR

1000

REVISED JAN., 1983

U.S.F.S. #J-4,5