

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

Register's Office }  
 Gogebic County } ss.

For corners in

Gogebic  
 (County)

Located in:

Corner Code #

1. Public Land Survey

T 44N R 41W

A-5, 3

T R

012

T R

001

2. Property Controlling  
in Section**PEER GROUP****Approved**3. Miscellaneous  
Property in Sec.**Richard L. Brown****5/25/94**

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

Closing corner between Sections 13 and 18 on Mich/Wisc State Line

I, Gary L. Pisoni, in a field survey on February 17, 1994 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William A. Burt, U.S. Deputy Surveyor in July, 1847.  
 Original corner: Cedar Post

Original Bearing Trees:

White Pine 7"  
 Tamarack 8"

N 12° E  
 N 15° W

24 links (15.84 feet)  
 42 links (27.72 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence found.

Corner restored by single proportionate measurement along the Mich/Wisc State boundary line on line between Mile Corner #31 and Mile Corner #31½.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, I set a 2" diameter by 30" long split base aluminum pipe monument with a 3" cast aluminum cap, stamped to read: T44N, R42W, R41W, S-13, S-18, Mich., Wis., C.C., 1991, RLS 27457 from which I established the following new blazed and scribed bearing trees: (all measurements taken to a nail in side of tree)

Black Spruce	5"	S 06° E	3.69 feet
Cedar	9"	N 79° W	26.95 feet
Hemlock	17"	N 06° E	37.35 feet
Steel sign post		N 70° E	1.10 feet



Signed by

Gary L. Pisoni

Date

4-12-94

Surveyor's Michigan License No.

27457

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 26, 1971  
 REVISED MAY 14, 1975  
 REVISED JAN., 1983