

Register's Office } ss.  
Gogebic County }

Gogebic  
(County)

Corner Code ~~##~~

T 45N R 41 W

C-12, 13

T \_\_\_\_\_ R \_\_\_\_\_

005

T \_\_\_\_\_ R \_\_\_\_\_

\_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

Age Group	Percentage of Respondents
18-24	65
25-34	75
35-44	80
45-54	85
55-64	90
65-74	95
75+	95

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

**Approved**

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

Richard L. Drach

5/25/94

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

## 5. Private Claims

Meander Corner between Sections 31 and 32.

[illegible]

A. Description of original monument and accessories and/or subsequent restoration:  
Original corner established by Algernon Merryweather, U.S. Deputy Surveyor on June 22nd, 1852.  
Original Corner: 5" Cedar corner tree  
Original bearing tree:

Tamarack	6"	S80°E	11 lks.(7.26 feet)
----------	----	-------	--------------------

Found rebar between Sections 31 and 32 set by Gourdie Fraser & Associates. Said rebar is approximately 40 feet North of Big Mosquito Lake shore line. The rebar was used in a lot subdivision on Grace and Spider lakes. I accepted the rebar as the best available evidence for restoring the West boundary line of Section 32. The rebar was used as a Witness Corner to project the West boundary line of Section 32 to the North shore of Big Mosquito Lake.

Hemlock	16"	N63°W	34.01 feet
Hemlock	13"	N21°E	24.85 feet
Cedar	8"	East	40.12 feet
Steel Sign Post		North	0.90 feet

Signed by Harry J. Brown

Date 4-12-94

Surveyor's Michigan License No. 27457

U.S.F.S. #Y,Z-5

