

Register's Office } ss.
Saginaw County }

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

GOGEBIC
(County)

Located In:

Corner Code #

1. Public Land Survey

T46NR 44W

K-2

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

SURVEY &
MONUMENTATION

JAN 05 2001

SECTION

Received for record the

26TH day of MAY

A. D. 1900 at 11:00 o'clock

A. m., and recorded in

Liber 7 of CORNERS

on page 322

Cheryl Ruppel
Deputy Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

Quarter corner, Sections 1 & 2, T46N, R44W

I, John P. Goss, in a field survey on May 5, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:
Corner established by Austin Burt, on August 20, 1851.

Original bearing trees: Yellow Birch 16" S 120° E 27 links (17.82ft.)
Hemlock 8" N 370° W 42 links (27.27 ft.)

Richard L. Drahn, 21564, on Sept. 16, 1982, restored corner position at record bearing and distance from the remains of the two original bearing trees. Further verified by measurements to natural feature calls. He set a 2" I.D. aluminum monument with a 3/4" aluminum cap, stamped to indicated the corner position. He established the following reference objects: 6" Red Maple - N 57° W - 20.52 ft. 6" White Spruce - N 73° E - 10.66 ft.; 4" Red Maple - S 02° E - 39.84 ft.;

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
6' metal sign post - N 04° W - 1.33 ft.

On March 15, 1983, he recorded said corner in Liber 2, page 396 of Land Corners

No original evidence found.

Found Richard L. Drahn, monument and accessories.

Act 74 research on file.

DEED GROUP APPROVED
Richard L. Drahn 05/24/00
COUNTY SAGINAW

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
From the found monument, stamped to read: T.46 N., R.44 W.; 1/4; S-1, S-2; 1982 R.L.S. 21564, from which I established the following existing and new reference objects:

9" Red Maple N 57° W 20.83 ft. new nail
8" White Spruce N 73° E 10.75 ft. new nail
6" Red Maple S 02° E 39.84 ft.
6" Red Maple Due West 17.03 ft.
6' metal sign post N 04° W 1.33 ft. to face
(All measurements taken to nail in side of tree)



Signed by John P. Goss

Date May 5, 2000

Surveyor's Michigan License No. 23509

U.S.F.S. No. C-21