

DEC 15 1998

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office } ss.
Gogebic County }

For corners in

SECTION

GOGEBIC
(County)

Located In:

Corner Code #

1. Public Land Survey

SECTION 36

T	R		
T 46NR	47W	M-12/13	003
T 46NR	46W	A-12/13	003
T	R		
T	R		
T	R		
T	R		
T	R		

2. Property Controlling
in Section

S

T R

3. Miscellaneous
Property in Sec.

S

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

CLOSING CORNER ON MI/WI STATE LINE
SECTIONS 36 & 31, T46N,R46-47W
JOHN R GARSKE OCT. 21, 98

I, _____, in a field survey on _____, 19____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Received for record the
30TH day of OCTOBER
A. D. 1998 at 9:05 o'clock
A M., and recorded in
Liber 7 of CORNERS
on page 71
Ramona Collins Deputy
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		

A. Description of original monument and accessories and/or subsequent restoration:

ORIGINAL TOWNSHIP SURVEY BY WILLIAM BURT, D.S. IN SEPT. 1847.
ORIGINAL CORNER: SPRUCE POST
ORIGINAL BEARING TREES:
Y.BIRCH 18" N17°W 20 LINKS
DO 12" N78°E 24 LINKS
1928-RESURVEY OF STATE LINE BY HARRINGTON, D.S.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I ESTABLISHED THE CLOSING CORNER BY SINGLE PROPORTIONAL MEASUREMENT ON THE MICHIGAN/ WISCONSIN STATE LINE BETWEEN MILE POST "0" ON THE EAST BANK OF THE MONTREAL RIVER AND MILE POST "1/2". DISTANCES BETWEEN BURT'S, HARRINGTON'S AND OUR SURVEY ARE SHOWN ON THE SKETCH ON THE BACK. A THOROUGH SEARCH OF THE AREA WAS MADE PRIOR TO MONUMENTING WITH NOTHING FOUND.

(RESEARCH ON FILE)

PEER GROUP APPROVED
Richard P. Deaton 10/27/98
COUNTY REGISTER-CLERK

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I SET A 2 1/2" X 30" ALUMINUM PIPE MONUMENT WITH A 3 1/4" DIA. ALUMINUM CAP STAMPED TO IDENTIFY THE CORNER FORM WHICH;
10" SUGAR MAPLE N22°E 13.59 FEET
7" SUGAR MAPLE S44°W 10.81 FEET
10" SUGAR MAPLE N78°W 11.44 FEET
STEEL SIGN RAIL S45°E 1.50 FEET



Signed by John R Garske
Surveyor's Michigan License No. 28410

Date 10-26-98