

SURVEY & REMONUMENTATION

JAN 05 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Register's Office }
Gogebic County }

For corners in
Gogebic
(County)

Located in: Corner Code #

1. Public Land Survey T46NR47W K-6-7
T R
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

Meander Corner common to Sections 13 and 14 on the Northern shore of the Montreal River.

I, John R. Garske, in a field survey on March 13, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and / or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Received for record the
2nd day of JUNE
A. D. 1900 at 10:20 o'clock
A m., and recorded in
Liber 7 of CORNERS
on page 357
Cheryl Ruppe, Dep
Register of Deeds

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	5		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and / or subsequent restoration:

Original survey by William Ives in 1848.
Original Corner: Wood post
Original Bearing Trees: 5" Fir N 16° W 37 Links
8" Fir N 27° E 52 Links

B. Description of corner evidence found and / or method applied in restoring or re-establishing corner:

No corner evidence found.
I set a 30" aluminum Bernsten monument on the North shore of the Montreal River at the end of an ancient fenceline from the North.

Record research on file.

ee sketch on back)

PEER GROUP APPROVED
Richard L. Drahn 5/24/00
COUNTY BOARD OF LAND SURVEYORS

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I set an aluminum monument, monumenting a witness corner to the meander corner common to Sections 13 & 14, from which I established the following witnesses:

13" Black Cherry	N 04° W	14.06 Feet
4" Black Cherry	N 70° W	24.65 Feet
4' Sign Post	S 10° W	1.40 Feet
4' Sign Post	S 75° E	7.52 Feet

Signed by John R. Garske

Surveyor's Michigan License No. 28410
FB # 213, page 120

Date 5/24/00



Quarter Corner common to Sections 13 & 14,
T 46 N, R 47 W.

K-6-7



Scale: 1" = 300'

SURVEY &
REMONUMENTATION

JAN 05 2001

SECTION

